

Light Measurement Report

Print date: 25-10-2024

Measurement date and time: 25-10-2024 09:51:35 – Measurement no. VFR-241025-1602-MS

Measurement tracking No. and Link: [VT241025-001147](#)

Operator:



Laboratory and Equipment

Laboratory Owner and Location

Goniospectrometer System and Type

Sensor Name, Calibr. Date and Serial No.

Spectrometer Manufacturer and Model

Viso Systems, Copenhagen V, Denmark

LabSpion – Type C, horizontal

LabSensor Model2 – 11-1-2024 – 3130191315

Ibsen Photonics, Denmark – Freedom VIS (Custom Viso)

Measurement Conditions

Number of C-planes and Resolution

γ (gamma)-Resolution

Test Distance

Input Power, Power and Displ. Factors

Input RMS Voltage and Current

Frequency of Input Power

Warm-up Time and Variation

72 planes – 5°

5°

2,49 m

39,2 W – PF 0,97 – DPF 0,98

230 V – 0,175 A

50 Hz

Lamp stabilized in 15 min 52 sec – 2,0%

Tested Light Source

Product Name

Item No. and Manufacturer

Product Description (line 1)

DA205V-4000K

DA205V-4000K – Dutchfulfillment

LED DOWNLIGHT | KANTELBAAR | Ø195 | 40W

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)

Efficiency

Peak Intensity and Beam Angle

Correlated Color Temperature, Target/Measured

Color Rendering Index

Color Rendering TM30-18

Color Shift, CIE duv and MacAdam Steps

Flicker

3488 lm – 0,12% / 99,88%

89 lm/W

10224 cd – 20,3°



CCT = 4000 K / 4236 K

CRI 91,8

R_f 91,1 – R_g 98,2

Duv 0,0023 – SDCM 5,1

SVM 0,01 – PstLM 0,02



Light Measurement Report

Print date: 25-10-2024

Measurement date and time: 25-10-2024 09:51:35 – Measurement no. VFR-241025-1602-MS


Measurement tracking No. and Link: [VT241025-001147](#)

Operator:



Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	3488 lm
Lumen Up% / Down%	0,12% / 99,88%
Peak Intensity	10224 cd
Beam Angle (50%)	20,3°
Beam Angle (90%)	20,3°
Beam Angle (10%)	20,3°

Cut-off Angle

Average 2,5%	97,1°
--------------	-------

Field Angle

Average 10%	81,2°
-------------	-------


Intensity Ratio

In 120° cone	98,6%
In 90° cone	93,3%

C000-C180

C090-C270

Linear distribution diagram - Intensity (candela) vs γ-angle




Light Measurement Report


Print date: 25-10-2024
Measurement date and time: 25-10-2024 09:51:35 – Measurement no. VFR-241025-1602-MS
Measurement tracking No. and Link: [VT241025-001147](#)
Operator:



Iso-intensity Diagram (Iso-candela)



Iso-illuminance Diagram (Iso-lux)



Light Measurement Report

Print date: 25-10-2024

Measurement date and time: 25-10-2024 09:51:35 – Measurement no. VFR-241025-1602-MS

Measurement tracking No. and Link: [VT241025-001147](#)

Operator:




Color details


Correlated Color Temperature, Target CCT = 4000 K
Correlated Color Temperature, Measured CCT = 4236 K
Color Rendering Index CRI 91,8
Color Rendering Index, R9 (red component) R9 = 51,7
Color Rendering TM30-18 R_f 91,1 – R_g 98,2
Color Quality Scale CQS = 91,6

MacAdam Steps
Color coordinates CIE 1931 (x;y) = (0,381;0,377)
Color coordinate CIEs 1960 (u;v) = (0,225;0,334)
Color deviation from BBL Duv = 0,0023
Color coordinate CIEs 1976 (CIELUV) (u';v') = (0,225;0,502)


CIE 1931



CIE 1931 – zoomed on Planckian locus




Color Rendering Index per reference color (CIE 1995)




CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
91,6	94,5	96,9	92,8	91,3	92,5	93,3	81,8	51,7	86,9	93,7	74,0	92,4	98,2	86,8

Spectral power distribution (SPD) / W/nm – 0-100%




TM30-18 R_f-values per hue bin



TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
89,2	92,4	89,6	94,0	94,0	96,9	96,3	94,9	92,7	88,8	86,7	90,5	90,0	92,6	85,9	85,6

Color Quality Scale by reference color



CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
89,0	98,4	88,4	88,3	91,9	93,2	94,0	95,4	99,0	95,4	94,8	94,2	93,6	85,7	87,0

Light Measurement Report

Print date: 25-10-2024

Measurement date and time: 25-10-2024 09:51:35 – Measurement no. VFR-241025-1602-MS

Measurement tracking No. and Link: [VT241025-001147](#)

Operator:



Light Planning – UGR table

Uncorrected, comprehensive UGR table according to 117-1995

Reflectances											
ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room size											
H = mounting height above eye level											
X	Y	Viewed Crosswise					Viewed Endwise				
		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
2H	2H	23,4	24,1	23,5	24,3	24,5	23,4	24,1	23,5	24,3	24,5
	3H	23,1	23,9	23,5	24,1	24,3	23,1	23,9	23,5	24,1	24,3
	4H	23,1	23,8	23,5	24,1	24,3	23,1	23,8	23,5	24,1	24,3
	6H	23,1	23,7	23,4	24,0	24,4	23,1	23,7	23,4	24,0	24,4
	8H	23,1	23,7	23,4	24,0	24,4	23,1	23,7	23,4	24,0	24,4
	12H	23,0	23,6	23,4	24,0	24,4	23,0	23,6	23,4	24,0	24,4
4H	2H	23,0	23,8	23,4	24,0	24,3	23,0	23,8	23,4	24,0	24,3
	3H	23,0	23,6	23,3	23,9	24,3	23,0	23,6	23,3	23,9	24,3
	4H	22,9	23,4	23,3	23,9	24,4	22,9	23,4	23,3	23,9	24,4
	6H	22,9	23,4	23,4	23,8	24,1	22,9	23,4	23,4	23,8	24,1
	8H	22,8	23,3	23,3	23,7	24,1	22,8	23,3	23,3	23,7	24,1
	12H	22,8	23,2	23,3	23,6	24,1	22,8	23,2	23,3	23,6	24,1
8H	4H	22,8	23,3	23,3	23,7	24,0	22,8	23,3	23,3	23,7	24,0
	6H	22,8	23,1	23,3	23,6	24,1	22,8	23,1	23,3	23,6	24,1
	8H	22,8	23,1	23,3	23,6	24,2	22,8	23,1	23,3	23,6	24,2
	12H	22,8	23,0	23,3	23,5	24,1	22,8	23,0	23,3	23,5	24,1
12H	4H	22,7	23,1	23,2	23,5	24,0	22,7	23,1	23,2	23,5	24,0
	6H	22,8	23,1	23,3	23,6	24,2	22,8	23,1	23,3	23,6	24,2
	8H	22,8	23,0	23,3	23,5	24,1	22,8	23,0	23,3	23,5	24,1
Variations with the observer position for the luminaire spacings, S:											
S = 1.0H		2,7 / -8,1					2,7 / -8,1				
S = 1.5H		5,0 / -9,0					5,0 / -9,0				
S = 2.0H		6,9 / -9,3					6,9 / -9,3				

Coefficients of Utilization

Ceiling reflectance	80			70			50			30			10			0		
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR		(RCR: Room Cavity Ratio)			Room Values are expressed as percentage of Lumen delivered to the task surface													
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93
2	108	103	99	95	105	101	97	94	98	95	92	95	92	90	92	90	88	87
3	102	96	91	87	100	94	90	86	92	88	85	89	86	83	87	84	82	80
4	97	90	84	80	95	88	83	79	86	82	78	84	80	77	82	79	76	75
5	92	84	78	74	91	83	78	73	81	76	73	79	75	72	78	74	71	70
6	88	79	73	69	86	78	73	68	77	72	68	75	71	68	74	70	67	66
7	84	74	69	64	82	74	68	64	73	67	64	71	67	63	70	66	63	62
8	80	70	65	61	79	70	64	60	69	64	60	68	63	60	67	63	60	58
9	76	67	61	57	75	66	61	57	65	60	57	65	60	57	64	60	56	55
10	73	64	58	54	72	63	58	54	62	57	54	62	57	54	61	57	54	52

Light Measurement Report


Print date: 25-10-2024
Measurement date and time: 25-10-2024 09:51:35 – Measurement no. VFR-241025-1602-MS
Measurement tracking No. and Link: [VT241025-001147](#)
Operator:



Luminaire budgetary diagram

Uncorrected, comprehensive UGR table according to 117-1995

LAMPS (number of lamps)



Conditions

H = Room height	Flux = 3488 lm	p(%)		
H _{down} = Lamp distance from ceiling =	0.00 m	Line type	Ceiling reflectance	Wall reflectance
H _{work} = Work area height from floor =	0.00 m	-----	70	50
E _{work} = Average lux on work area =	100 lx	-----	50	30
				Floor reflectance
				20

Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
715 lm	788 lm	678 lm	770 lm	441 lm	48,5 lm	21,3 lm	17,6 lm	4,27 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0,599 lm	0,338 lm	0,374 lm	0,443 lm	0,491 lm	0,580 lm	0,692 lm	0,642 lm	0,181 lm

Light Measurement Report

Print date: 25-10-2024

Measurement date and time: 25-10-2024 09:51:35 – Measurement no. VFR-241025-1602-MS

Measurement tracking No. and Link: [VT241025-001147](#)

Operator:



Outdoor Light Planning

Lumen per Zone

Zone (γ)	Lumen	% Total
0-10°	715 lm	20,5%
10-20°	788 lm	22,6%
20-30°	678 lm	19,4%
30-40°	770 lm	22,1%
40-50°	441 lm	12,6%
50-60°	48 lm	1,4%
60-70°	21 lm	0,6%
70-80°	18 lm	0,5%
80-90°	4 lm	0,1%
90-100°	1 lm	0,0%
100-110°	0 lm	0,0%
110-120°	0 lm	0,0%
120-130°	0 lm	0,0%
130-140°	0 lm	0,0%
140-150°	1 lm	0,0%
150-160°	1 lm	0,0%
160-170°	1 lm	0,0%
170-180°	0 lm	0,0%
Total	3488 lm	100,0%

Intensity peaks

Max intensity	10224 cd
Intensity, 90°	1 cd
Intensity, 0°	10224 cd

Zonal Lumen summary

Zone (γ)	Lumen	% Total
0-30°	2181 lm	62,5%
0-40°	2951 lm	84,6%
0-60°	3440 lm	98,6%
60-90°	43 lm	1,2%
70-100°	22 lm	0,6%
90-120°	1 lm	0,0%
0-90°	3483 lm	99,9%
90-180°	4 lm	0,1%
0-180°	3488 lm	100,0%

BUG rating

	Lumen	% Total
Forward light		
Low(0-30°)	1093 lm	31,3%
Medium(30-60°)	627 lm	18,0%
High(60-80°)	19 lm	0,6%
Very high(80-90°)	2 lm	0,1%
Back light		
Low(0-30°)	1093 lm	31,3%
Medium(30-60°)	627 lm	18,0%
High(60-80°)	19 lm	0,6%
Very high(80-90°)	2 lm	0,1%


Uplight

Low(90-100°)	1 lm	0,0%
High(100-180°)	4 lm	0,1%

IESNA TM-15-07

Luminaire Classification System For Outdoor Luminaires

BUG rating B3 U1 G0



Light Measurement Report

Print date: 25-10-2024
Measurement date and time: 25-10-2024 09:51:35 – Measurement no. VFR-241025-1602-MS
Measurement tracking No. and Link: [VT241025-001147](#)
Operator:




Power Details


Input Power

Power feed to light source	39,2 W
Frequency of input power	50 Hz
RMS Input voltage feed, V_{RMS}	230 V
RMS Input current feed, I_{RMS}	0,175 A
Volt-Ampere or apparent power = $V_{RMS} * I_{RMS}$	40,33 VA
Displacement factor of AC power feed	0,98
Power factor of AC current feed	0,97
Total harmonic distortion of the current	9,68%
Total harmonic distortion of the voltage	0,07%

Input Power Curve



Efficiency



Stabilization Details

Warmup Conditions

Stable period	15 min
Stable change max	2,0%
Minimum time	15 min

Color Temperature Change

CCT start	3965 K
CCT shift	+35 K
CCT end	4000 K


Warmup Result

Total warmup time	Lamp stabilized in 15 min 52 sec
Warmup variation	-2,3%

Output Change

Output start	3568 lm
Output change	-81 lm
Output end	3488 lm

Stabilization Curve



Light Measurement Report


Print date: 25-10-2024
Measurement date and time: 25-10-2024 09:51:35 – Measurement no. VFR-241025-1602-MS
Measurement tracking No. and Link: [VT241025-001147](#)
Operator:



Flicker /TLA details

Flicker Meter Type	Viso Systems LabFlicker	Measurement time	
Frequency of input power	50 Hz	PstLM	180 sec
Flicker/TLA sample rate	20000 samples/s	All other indices	1,2 sec
Flicker indices according to Illuminating Engineering Society (IES)		Flicker indices according to California Energy Commission (CEC) 2016b	
Flicker frequency	100 Hz	JA8/10 40 Hz	0,02 %
Percent Flicker	0,21 %	JA8/10 90 Hz	0,03 %
Flicker index	0	JA8/10 200 Hz	0,2 %
TLA indices (re IEC TR 61547-1, IEC 61000-3-3 and IEC 61000-4-15)		JA8/10 400 Hz	0,2 %
PstLM value (F < 80 Hz)	0,02	JA8/10 1000 Hz	0,2 %
SVM value (80 < F < 2000 Hz)	0,01	Flicker indices according to Lighting Research Center (2015)	
		Perception metric, Assist Mp	0,01

Flicker frame (frame of one flicker period in time domain)



Flicker FFT (flicker curve in frequency domain)



IEEE 1789 Frequency/modulation plot

