

Light Measurement Report

Print date: 29-4-2025

Measurement date and time: 29-4-2025 13:07:18 – Measurement no. VFR-250429-0964-MS

Measurement tracking No. and Link: [VT250429-007441](https://www.viso-systems.com/track/VT250429-007441)

Operator:



Laboratory and Equipment

Laboratory Owner and Location
Goniospectrometer System and Type
Sensor Name, Calibr. Date and Serial No.
Spectrometer Manufacturer and Model

Viso Systems, Copenhagen V, Denmark
LabSpion – Type C, horizontal
LabSensor Model2 – 11-1-2024 – 3130191315
Ibsen Photonics, Denmark – Freedom VIS (Custom Viso)

Measurement Conditions

Number of C-planes and Resolution
 γ (gamma)-Resolution
Test Distance
Input Power, Power and Displ. Factors
Input RMS Voltage and Current
Frequency of Input Power
Warm-up Time and Variation

12 planes – 30°
5°
3,47 m
155,1 W – PF 0,98 – DPF 0,98
230 V – 0,689 A
50 Hz
Lamp stabilized in 15 min 2 sec – 2,0%

Tested Light Source



Product Name
Item No. and Manufacturer
Product Description (line 1)

278455-6000K-150W
278455-6000K-150W – Dutchfulfillment
LED HIGHBAY | ANANKE | 90° | 150W/120W/80W | CCT SWITCH

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)
Efficiency
Peak Intensity and Beam Angle
Correlated Color Temperature, Target/Measured
Color Rendering Index
Color Rendering TM30-18
Color Shift, CIE duv and MacAdam Steps
Flicker

20898 lm – 0,13% / 99,87%
135 lm/W
10132 cd – 91°
CCT = 6000 K / 5720 K
CRI 81,8
 R_f 82,0 – R_g 93,4
Duv 0,0031 – SDCM 5,5
SVM 0 – PstLM 0,02



Light Measurement Report

Print date: 29-4-2025

Measurement date and time: 29-4-2025 13:07:18 – Measurement no. VFR-250429-0964-MS


Measurement tracking No. and Link: [VT250429-007441](https://www.viso-systems.com/VT250429-007441)

Operator:



Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	20898 lm
Lumen Up% / Down%	0,13% / 99,87%
Peak Intensity	10132 cd
Beam Angle (50%)	91°
Beam Angle (90%)	91°
Beam Angle (10%)	91°

Cut-off Angle

Average 2,5%	157,7°
--------------	--------

Field Angle

Average 10%	135,1°
-------------	--------


Intensity Ratio

In 120° cone	91,2%
In 90° cone	70,3%

C000-C180

C090-C270

Linear distribution diagram - Intensity (candela) vs γ -angle



Light Measurement Report

Print date: 29-4-2025


Measurement date and time: 29-4-2025 13:07:18 – Measurement no. VFR-250429-0964-MS

Measurement tracking No. and Link: [VT250429-007441](https://www.viso-systems.com/VT250429-007441)

Operator:



Iso-intensity Diagram (Iso-candela)




90 %	9118,5 cd
80 %	8105,3 cd
70 %	7092,1 cd
60 %	6079,0 cd
50 %	5065,8 cd
40 %	4052,7 cd
30 %	3039,5 cd
20 %	2026,3 cd
10 %	1013,2 cd

Peak intensity: 10131,6 cd

Number of c-planes: 12

Iso-illuminance Diagram (Iso-lux)



50,0 %	562,9 lx
30,0 %	337,7 lx
10,0 %	112,6 lx
5,0 %	56,3 lx
3,0 %	33,8 lx

Peak illuminance: 1125,7 lx

Mounting height: 3,0 m

Number of c-planes: 12

Light Measurement Report

Print date: 29-4-2025

Measurement date and time: 29-4-2025 13:07:18 – Measurement no. VFR-250429-0964-MS

Measurement tracking No. and Link: [VT250429-007441](https://www.viso-systems.com/VT250429-007441)

Operator:




Color details


Correlated Color Temperature, Target CCT = 6000 K
 Correlated Color Temperature, Measured CCT = 5720 K
 Color Rendering Index CRI 81,8
 Color Rendering Index, R9 (red component) R9 = -3,4
 Color Rendering TM30-18 R_f 82,0 – R_g 93,4
 Color Quality Scale CQS = 78,9

MacAdam Steps
 Color coordinates CIE 1931 (x;y) = (0,322;0,332)
 Color coordinate CIEs 1960 (u;v) = (0,203;0,314)
 Color deviation from BBL Duv = 0,0031
 Color coordinate CIEs 1976 (CIELUV) (u';v') = (0,203;0,471)


CIE 1931



CIE 1931 – zoomed on Planckian locus




Color Rendering Index per reference color (CIE 1995)




CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
79,7	88,3	92,8	80,5	80,1	82,6	86,0	64,6	-3,4	71,4	79,5	56,5	82,4	96,4	73,2

Spectral power distribution (SPD) / W/nm – 0-100%




TM30-18 R_f-values per hue bin



TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
73,0	82,2	78,3	86,3	87,4	94,3	89,9	84,5	82,5	72,4	73,3	89,4	86,1	82,2	70,0	83,6

Color Quality Scale by reference color



CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
80,5	98,5	76,0	69,6	75,9	79,2	83,7	88,1	96,8	86,0	80,9	79,3	79,0	66,5	72,0

Light Measurement Report

Print date: 29-4-2025


Measurement date and time: 29-4-2025 13:07:18 – Measurement no. VFR-250429-0964-MS

Measurement tracking No. and Link: [VT250429-007441](https://www.viso-systems.com/VT250429-007441)

Operator:



Beam Details



Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3,3	6,6	9,8	13,1	16,4	19,7	23	26,2	29,5	32,8	36,1	39,4	42,7	45,9	49,2	52,5	55,8	59,1	62,3	65,6	ft
10132	2533	1126	633	405	281	207	158	125	101	84	70	60	52	45	40	35	31	28	25	lux
941,3	235,3	104,6	58,8	37,7	26,1	19,2	14,7	11,6	9,4	7,8	6,5	5,6	4,8	4,2	3,7	3,3	2,9	2,6	2,4	fc

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
10,1K	10,1K	10,0K	9,7K	9,4K	8,9K	8,3K	7,5K	6,4K	5,2K	3,9K	2,8K	1,9K	1,3K	0,8K	0,5K	0,2K	0,0K	0,0K	0,0K	cd
100%	100%	98%	96%	93%	88%	82%	74%	64%	51%	39%	28%	19%	13%	8%	5%	2%	0%	0%	0%	of 0°val

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
10,1K	10,1K	10,0K	9,7K	9,4K	8,9K	8,3K	7,5K	6,4K	5,2K	3,9K	2,8K	1,9K	1,3K	0,8K	0,5K	0,2K	0,0K	0,0K	0,0K	cd
100%	100%	98%	96%	93%	88%	82%	74%	64%	51%	39%	28%	19%	13%	8%	5%	2%	0%	0%	0%	of 0°val

Intensities in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
10,1K	10,1K	10,0K	9,7K	9,4K	8,9K	8,3K	7,5K	6,4K	5,2K	3,9K	2,8K	1,9K	1,3K	0,8K	0,5K	0,2K	0,0K	0,0K	0,0K	cd
100%	100%	98%	96%	93%	88%	82%	74%	64%	51%	39%	28%	19%	13%	8%	5%	2%	0%	0%	0%	of 0°val

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
10,1K	10,1K	10,0K	9,7K	9,4K	8,9K	8,3K	7,5K	6,4K	5,2K	3,9K	2,8K	1,9K	1,3K	0,8K	0,5K	0,2K	0,0K	0,0K	0,0K	cd
100%	100%	98%	96%	93%	88%	82%	74%	64%	51%	39%	28%	19%	13%	8%	5%	2%	0%	0%	0%	of 0°val

Light Measurement Report

Print date: 29-4-2025

Measurement date and time: 29-4-2025 13:07:18 – Measurement no. VFR-250429-0964-MS

Measurement tracking No. and Link: [VT250429-007441](#)

Operator:



Light Planning – UGR table

Uncorrected, comprehensive UGR table according to 117-1995

Reflectances		70	70	50	50	30	70	70	50	50	30
	ρ Ceiling	70	70	50	50	30	70	70	50	50	30
	ρ Walls	50	30	50	30	30	50	30	50	30	30
	ρ Floor	20	20	20	20	20	20	20	20	20	20
Room size		Viewed Crosswise					Viewed Endwise				
H = mounting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	Y										
2H	2H	28,5	29,5	28,7	29,8	30,0	28,5	29,5	28,7	29,8	30,0
	3H	28,8	29,9	29,2	30,2	30,3	28,8	29,9	29,2	30,2	30,3
	4H	28,9	30,0	29,3	30,2	30,5	28,9	30,0	29,3	30,2	30,5
	6H	29,0	29,9	29,3	30,2	30,6	29,0	29,9	29,3	30,2	30,6
	8H	29,0	29,9	29,3	30,2	30,6	29,0	29,9	29,3	30,2	30,6
	12H	29,0	29,8	29,3	30,1	30,6	29,0	29,8	29,3	30,1	30,6
4H	2H	28,6	29,6	29,0	29,9	30,2	28,6	29,6	29,0	29,9	30,2
	3H	29,2	30,1	29,6	30,4	30,8	29,2	30,1	29,6	30,4	30,8
	4H	29,3	30,1	29,8	30,5	31,0	29,3	30,1	29,8	30,5	31,0
	6H	29,4	30,1	29,9	30,5	30,9	29,4	30,1	29,9	30,5	30,9
	8H	29,4	30,1	29,9	30,4	30,8	29,4	30,1	29,9	30,4	30,8
	12H	29,3	29,9	29,8	30,3	30,8	29,3	29,9	29,8	30,3	30,8
8H	4H	29,4	30,0	29,9	30,4	30,8	29,4	30,0	29,9	30,4	30,8
	6H	29,5	30,0	30,0	30,4	31,0	29,5	30,0	30,0	30,4	31,0
	8H	29,5	29,9	30,0	30,4	31,1	29,5	29,9	30,0	30,4	31,1
	12H	29,5	29,8	30,1	30,3	30,9	29,5	29,8	30,1	30,3	30,9
12H	4H	29,3	29,9	29,8	30,3	30,8	29,3	29,9	29,8	30,3	30,8
	6H	29,5	29,9	30,0	30,4	31,0	29,5	29,9	30,0	30,4	31,0
	8H	29,5	29,8	30,1	30,3	30,9	29,5	29,8	30,1	30,3	30,9

Variations with the observer position for the luminaire spacings, S:

S = 1.0H	0,4 / -0,7	0,4 / -0,7
S = 1.5H	1,1 / -1,6	1,1 / -1,6
S = 2.0H	2,3 / -2,8	2,3 / -2,8

Coefficients of Utilization

Ceiling reflectance	80	70	50	30	10	0										
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	0	
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0	
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumen delivered to the task surface															
0	119	119	119	119	116	116	116	116	111	111	106	106	106	102	102	100
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	93	88
2	103	96	90	86	100	94	89	85	91	86	83	88	84	81	85	77
3	95	86	79	74	93	85	78	73	82	76	72	79	74	71	77	67
4	88	78	70	64	86	76	69	64	74	68	63	72	66	62	70	59
5	82	70	62	57	80	69	62	56	67	61	56	65	60	55	64	53
6	76	64	56	50	74	63	56	50	61	55	50	60	54	49	58	47
7	71	58	51	45	69	58	50	45	56	49	45	55	49	44	54	42
8	66	54	46	41	65	53	46	41	52	45	40	51	45	40	49	38
9	62	50	42	37	61	49	42	37	48	41	37	47	41	36	46	35
10	58	46	39	34	57	45	38	34	44	38	34	44	38	33	43	32

Light Measurement Report

Print date: 29-4-2025

Measurement date and time: 29-4-2025 13:07:18 – Measurement no. VFR-250429-0964-MS

Measurement tracking No. and Link: [VT250429-007441](#)


Operator:



Luminaire budgetary diagram

Uncorrected, comprehensive UGR table according to 117-1995

LAMPS (number of lamps)



Conditions

H = Room height	Flux = 20898 lm			
H _{down} = Lamp distance from ceiling =	0.00 m	Line type	Ceiling reflectance	ρ(%)
H _{work} = Work area height from floor =	0.00 m		Wall reflectance	Floor reflectance
E _{work} = Average lux on work area =	100 lx	-----	70	50
		————	50	30
				20

Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
961 lm	2753 lm	4125 lm	4690 lm	3999 lm	2527 lm	1275 lm	495 lm	43,8 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0,487 lm	1,20 lm	2,60 lm	4,00 lm	4,91 lm	5,30 lm	4,85 lm	3,44 lm	1,28 lm

Light Measurement Report

Print date: 29-4-2025

Measurement date and time: 29-4-2025 13:07:18 – Measurement no. VFR-250429-0964-MS

Measurement tracking No. and Link: [VT250429-007441](https://www.viso-systems.com/VT250429-007441)

Operator:



Outdoor Light Planning

Lumen per Zone

Zone (γ)	Lumen	% Total
0-10°	961 lm	4,6%
10-20°	2753 lm	13,2%
20-30°	4125 lm	19,7%
30-40°	4690 lm	22,4%
40-50°	3999 lm	19,1%
50-60°	2527 lm	12,1%
60-70°	1275 lm	6,1%
70-80°	495 lm	2,4%
80-90°	44 lm	0,2%
90-100°	0 lm	0,0%
100-110°	1 lm	0,0%
110-120°	3 lm	0,0%
120-130°	4 lm	0,0%
130-140°	5 lm	0,0%
140-150°	5 lm	0,0%
150-160°	5 lm	0,0%
160-170°	3 lm	0,0%
170-180°	1 lm	0,0%
Total	20898 lm	100,0%

Intensity peaks

Max intensity	10132 cd
Intensity, 90°	1 cd
Intensity, 0°	10132 cd

Zonal Lumen summary


Zone (γ)	Lumen	% Total
0-30°	7840 lm	37,5%
0-40°	12529 lm	60,0%
0-60°	19056 lm	91,2%
60-90°	1814 lm	8,7%
70-100°	540 lm	2,6%
90-120°	4 lm	0,0%
0-90°	20870 lm	99,9%
90-180°	28 lm	0,1%
0-180°	20898 lm	100,0%

BUG rating

	Lumen	% Total
Forward light		
Low(0-30°)	3907 lm	18,7%
Medium(30-60°)	5598 lm	26,8%
High(60-80°)	900 lm	4,3%
Very high(80-90°)	30 lm	0,1%
Back light		
Low(0-30°)	3907 lm	18,7%
Medium(30-60°)	5598 lm	26,8%
High(60-80°)	900 lm	4,3%
Very high(80-90°)	30 lm	0,1%
Uplight		
Low(90-100°)	1 lm	0,0%
High(100-180°)	28 lm	0,1%

IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B4 U2 G1



Light Measurement Report

Print date: 29-4-2025

Measurement date and time: 29-4-2025 13:07:18 – Measurement no. VFR-250429-0964-MS

Measurement tracking No. and Link: [VT250429-007441](#)

Operator:




Power Details


Input Power

Power feed to light source	155,1 W
Frequency of input power	50 Hz
RMS Input voltage feed, V_{RMS}	230 V
RMS Input current feed, I_{RMS}	0,689 A
Volt-Ampere or apparent power = $V_{RMS} * I_{RMS}$	158,31 VA
Displacement factor of AC power feed	0,98
Power factor of AC current feed	0,98
Total harmonic distortion of the current	6,2%
Total harmonic distortion of the voltage	0,08%

Input Power Curve



Efficiency



Stabilization Details

Warmup Conditions

Stable period	15 min
Stable change max	2,0%
Minimum time	15 min

Color Temperature Change

CCT start	5987 K
CCT shift	+13 K
CCT end	6000 K


Warmup Result

Total warmup time	Lamp stabilized in 15 min 2 sec
Warmup variation	-0,3%

Output Change

Output start	20955 lm
Output change	-58 lm
Output end	20898 lm

Stabilization Curve



Light Measurement Report

Print date: 29-4-2025

Measurement date and time: 29-4-2025 13:07:18 – Measurement no. VFR-250429-0964-MS

Measurement tracking No. and Link: [VT250429-007441](https://www.viso-systems.com/VT250429-007441)

Operator:



Flicker /TLA details

Flicker Meter Type Viso Systems LabFlicker
 Frequency of input power 50 Hz
 Flicker/TLA sample rate 20000 samples/s

Measurement time
 PstLM 180 sec
 All other indices 1,2 sec

Flicker indices according to Illuminating Engineering Society (IES)

Flicker frequency 97,09 Hz
 Percent Flicker 0,18 %
 Flicker index 0

Flicker indices according to California Energy Commission (CEC) 2016b

JA8/10 40 Hz 0,03 %
 JA8/10 90 Hz 0,05 %
 JA8/10 200 Hz 0,16 %
 JA8/10 400 Hz 0,17 %
 JA8/10 1000 Hz 0,18 %


TLA indices (re IEC TR 61547-1, IEC 61000-3-3 and IEC 61000-4-15)

PstLM value (F < 80 Hz) 0,02
 SVM value (80 < F < 2000 Hz) 0

Flicker indices according to Lighting Research Center (2015)

Perception metric, Assist Mp 0,02

Flicker frame (frame of one flicker period in time domain)



Flicker FFT (flicker curve in frequency domain)



IEEE 1789 Frequency/modulation plot

