

# Light Measurement Report

Print date: 14-4-2025

Measurement date and time: 14-4-2025 14:59:20 – Measurement no. VFR-250414-0761-MS

Measurement tracking No. and Link: [VT250414-000886](https://www.viso-systems.com/VT250414-000886)

Operator:



## Laboratory and Equipment

Laboratory Owner and Location  
Goniospectrometer System and Type  
Sensor Name, Calibr. Date and Serial No.  
Spectrometer Manufacturer and Model

Viso Systems, Copenhagen V, Denmark  
LabSpion – Type C, horizontal  
LabSensor Model2 – 11-1-2024 – 3130191315  
Ibsen Photonics, Denmark – Freedom VIS (Custom Viso)

## Measurement Conditions

Number of C-planes and Resolution  
 $\gamma$  (gamma)-Resolution  
Test Distance  
Input Power, Power and Displ. Factors  
Input RMS Voltage and Current  
Frequency of Input Power  
Warm-up Time and Variation

72 planes – 5°  
5°  
2,49 m  
28,3 W – PF 0,97 – DPF 0,98  
230 V – 0,126 A  
50 Hz  
Lamp stabilized in 15 min 2 sec – 2,0%

## Tested Light Source



Product Name  
Item No. and Manufacturer  
Product Description (line 1)

278899-3000K BATCH 2502  
278899-3000K BATCH 2502 – Dutchfulfillment  
LED DOWNLIGHT | KANTELBAAR | Ø145 | 28W | WIT | CCT-SWITCH

## Main Light Measurement Results

Output – Total Lumen (Up% / Down%)  
Efficiency  
Peak Intensity and Beam Angle  
Correlated Color Temperature, Target/Measured  
Color Rendering Index  
Color Rendering TM30-18  
Color Shift, CIE duv and MacAdam Steps  
Flicker

2367 lm – 0,08% / 99,92%  
84 lm/W  
5802 cd – 36,6°  
CCT = 3000 K / 3448 K  
CRI 93,2  
 $R_f$  90,9 –  $R_g$  97,6  
Duv -0,0012 – SDCM 14,1  
SVM 0,01 – PstLM 0,02



# Light Measurement Report

Print date: 14-4-2025

Measurement date and time: 14-4-2025 14:59:20 – Measurement no. VFR-250414-0761-MS


Measurement tracking No. and Link: [VT250414-000886](#)

Operator:



## Luminous Intensity diagram

Unit: 0-100% of peak intensity



## Main Values

Output (total Lumen)	2367 lm
Lumen Up% / Down%	0,08% / 99,92%
Peak Intensity	5802 cd
Beam Angle (50%)	36,6°
Beam Angle (90%)	36,6°
Beam Angle (10%)	36,6°

## Cut-off Angle

Average 2,5%	73°
--------------	-----

## Field Angle

Average 10%	58,5°
-------------	-------


## Intensity Ratio

In 120° cone	98,7%
In 90° cone	96,3%

**C000-C180**

**C090-C270**

## Linear distribution diagram - Intensity (candela) vs $\gamma$ -angle



# Light Measurement Report

Print date: 14-4-2025


Measurement date and time: 14-4-2025 14:59:20 – Measurement no. VFR-250414-0761-MS

Measurement tracking No. and Link: [VT250414-000886](#)

Operator:



## Iso-intensity Diagram (Iso-candela)




90 %	5222,1 cd
80 %	4641,9 cd
70 %	4061,6 cd
60 %	3481,4 cd
50 %	2901,2 cd
40 %	2320,9 cd
30 %	1740,7 cd
20 %	1160,5 cd
10 %	580,2 cd

Peak intensity: 5802,3 cd

Number of c-planes: 72

## Iso-illuminance Diagram (Iso-lux)



50,0 %	322,4 lx
30,0 %	193,4 lx
10,0 %	64,5 lx
5,0 %	32,2 lx
3,0 %	19,3 lx

Peak illuminance: 644,7 lx

Mounting height: 3,0 m

Number of c-planes: 72

# Light Measurement Report

Print date: 14-4-2025

Measurement date and time: 14-4-2025 14:59:20 – Measurement no. VFR-250414-0761-MS

Measurement tracking No. and Link: [VT250414-000886](https://www.viso-systems.com/VT250414-000886)

Operator:




## Color details

Correlated Color Temperature, Target CCT = 3000 K  
 Correlated Color Temperature, Measured CCT = 3448 K  
 Color Rendering Index CRI 93,2  
 Color Rendering Index, R9 (red component) R9 = 53,6  
 Color Rendering TM30-18 R<sub>f</sub> 90,9 – R<sub>g</sub> 97,6  
 Color Quality Scale CQS = 92,2

MacAdam Steps SDCM = 14,1  
 Color coordinates CIE 1931 (x;y) = (0,437;0,404)  
 Color coordinate CIEs 1960 (u;v) = (0,251;0,348)  
 Color deviation from BBL Duv = -0,0012  
 Color coordinate CIEs 1976 (CIELUV) (u';v') = (0,251;0,521)


CIE 1931



CIE 1931 – zoomed on Planckian locus




Color Rendering Index per reference color (CIE 1995)




CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
95,1	99,0	97,0	94,6	95,1	95,6	89,8	79,4	53,6	97,3	97,5	80,0	97,0	99,2	89,1

Spectral power distribution (SPD) / W/nm – 0-100%




TM30-18 R<sub>f</sub>-values per hue bin



TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
88,9	92,4	93,2	94,7	93,2	96,9	93,0	94,9	91,6	88,6	88,7	88,6	90,0	85,8	86,2	85,6

Color Quality Scale by reference color



CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
87,1	96,4	91,6	90,6	93,4	95,7	96,1	95,2	97,8	97,6	96,8	95,1	93,7	86,1	86,6

# Light Measurement Report

Print date: 14-4-2025


Measurement date and time: 14-4-2025 14:59:20 – Measurement no. VFR-250414-0761-MS

Measurement tracking No. and Link: [VT250414-000886](https://www.viso-systems.com/VT250414-000886)

Operator:



## Beam Details



### Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3,3	6,6	9,8	13,1	16,4	19,7	23	26,2	29,5	32,8	36,1	39,4	42,7	45,9	49,2	52,5	55,8	59,1	62,3	65,6	ft
5802	1451	645	363	232	161	118	91	72	58	48	40	34	30	26	23	20	18	16	15	lux
539,1	134,8	59,9	33,7	21,6	15	11	8,4	6,7	5,4	4,5	3,7	3,2	2,8	2,4	2,1	1,9	1,7	1,5	1,3	fc

### Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
5802	5802	5698	5577	5375	5032	4688	4145	3569	2993	2418	1843	1420	1022	700	507	315	230	162	111	cd
100%	100%	98%	96%	93%	87%	81%	71%	62%	52%	42%	32%	24%	18%	12%	9%	5%	4%	3%	2%	of 0°val

### Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
5802	5802	5698	5577	5375	5032	4688	4145	3569	2993	2418	1843	1420	1022	700	507	315	230	162	111	cd
100%	100%	98%	96%	93%	87%	81%	71%	62%	52%	42%	32%	24%	18%	12%	9%	5%	4%	3%	2%	of 0°val

### Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
5802	5802	5698	5577	5375	5032	4688	4145	3569	2993	2418	1843	1420	1022	700	507	315	230	162	111	cd
100%	100%	98%	96%	93%	87%	81%	71%	62%	52%	42%	32%	24%	18%	12%	9%	5%	4%	3%	2%	of 0°val

### Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
5802	5802	5698	5577	5375	5032	4688	4145	3569	2993	2418	1843	1420	1022	700	507	315	230	162	111	cd
100%	100%	98%	96%	93%	87%	81%	71%	62%	52%	42%	32%	24%	18%	12%	9%	5%	4%	3%	2%	of 0°val

# Light Measurement Report

Print date: 14-4-2025

Measurement date and time: 14-4-2025 14:59:20 – Measurement no. VFR-250414-0761-MS

Measurement tracking No. and Link: [VT250414-000886](https://www.viso-systems.com/VT250414-000886)

Operator:



## Light Planning – UGR table

Uncorrected, comprehensive UGR table according to 117-1995

Reflectances		70	70	50	50	30	70	70	50	50	30
	ρ Ceiling	70	70	50	50	30	70	70	50	50	30
	ρ Walls	50	30	50	30	30	50	30	50	30	30
	ρ Floor	20	20	20	20	20	20	20	20	20	20
Room size		Viewed Crosswise					Viewed Endwise				
H = mounting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	Y										
2H	2H	16,0	16,5	16,1	16,7	16,9	16,0	16,5	16,1	16,7	16,9
	3H	16,2	16,8	16,6	17,0	17,2	16,2	16,8	16,6	17,0	17,2
	4H	16,2	16,8	16,6	17,1	17,3	16,2	16,8	16,6	17,1	17,3
	6H	16,2	16,7	16,5	17,0	17,4	16,2	16,7	16,5	17,0	17,4
	8H	16,2	16,7	16,5	17,0	17,4	16,2	16,7	16,5	17,0	17,4
	12H	16,1	16,6	16,5	17,0	17,4	16,1	16,6	16,5	17,0	17,4
4H	2H	16,0	16,7	16,4	16,9	17,1	16,0	16,7	16,4	16,9	17,1
	3H	16,5	17,0	16,8	17,3	17,7	16,5	17,0	16,8	17,3	17,7
	4H	16,4	16,9	16,8	17,3	17,8	16,4	16,9	16,8	17,3	17,8
	6H	16,4	16,9	16,9	17,2	17,6	16,4	16,9	16,9	17,2	17,6
	8H	16,3	16,8	16,8	17,1	17,5	16,3	16,8	16,8	17,1	17,5
	12H	16,3	16,6	16,8	17,0	17,5	16,3	16,6	16,8	17,0	17,5
8H	4H	16,3	16,8	16,9	17,1	17,5	16,3	16,8	16,9	17,1	17,5
	6H	16,3	16,6	16,8	17,1	17,6	16,3	16,6	16,8	17,1	17,6
	8H	16,3	16,6	16,8	17,1	17,7	16,3	16,6	16,8	17,1	17,7
	12H	16,3	16,5	16,8	17,0	17,6	16,3	16,5	16,8	17,0	17,6
12H	4H	16,3	16,6	16,8	17,0	17,5	16,3	16,6	16,8	17,0	17,5
	6H	16,3	16,5	16,8	17,1	17,7	16,3	16,5	16,8	17,1	17,7
	8H	16,3	16,5	16,8	17,0	17,6	16,3	16,5	16,8	17,0	17,6

### Variations with the observer position for the luminaire spacings, S:

S = 1.0H	3,5 / -1,9	3,5 / -1,9
S = 1.5H	5,8 / -2,4	5,8 / -2,4
S = 2.0H	7,5 / -4,1	7,5 / -4,1

## Coefficients of Utilization

Ceiling reflectance	80			70			50			30			10			0		
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)																	
	Room Values are expressed as percentage of Lumen delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	112	110	108	112	110	108	106	106	104	103	102	101	100	99	98	97	95
2	110	106	102	99	108	104	101	98	101	98	96	98	96	94	95	94	92	91
3	106	100	96	93	104	99	95	92	96	93	90	94	91	89	92	90	88	86
4	101	95	91	87	100	94	90	87	92	89	86	90	87	85	88	86	84	82
5	98	91	86	83	96	90	86	82	88	84	81	87	83	81	85	82	80	79
6	94	87	82	79	93	86	82	78	85	81	78	83	80	77	82	79	77	76
7	91	83	78	75	90	83	78	75	82	77	74	80	77	74	79	76	74	73
8	88	80	75	72	87	80	75	72	79	74	71	78	74	71	77	73	71	70
9	85	77	72	69	84	77	72	69	76	72	69	75	71	68	74	71	68	67
10	82	74	70	66	81	74	69	66	73	69	66	72	69	66	72	68	66	65

# Light Measurement Report

Print date: 14-4-2025

Measurement date and time: 14-4-2025 14:59:20 – Measurement no. VFR-250414-0761-MS

Measurement tracking No. and Link: [VT250414-000886](https://vt250414-000886)


Operator:



## Luminaire budgetary diagram

Uncorrected, comprehensive UGR table according to 117-1995

LAMPS (number of lamps)



### Conditions

H = Room height	Flux = 2367 lm	$\rho(\%)$			
H <sub>down</sub> = Lamp distance from ceiling =	0.00 m	Line type	Ceiling reflectance	Wall reflectance	Floor reflectance
H <sub>work</sub> = Work area height from floor =	0.00 m	-----	70	50	30
E <sub>work</sub> = Average lux on work area =	100 lx	_____	50	30	20

### Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
528 lm	1057 lm	548 lm	121 lm	45,6 lm	35,9 lm	22,7 lm	5,51 lm	0,306 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0,012 lm	0,023 lm	0,018 lm	0,121 lm	0,060 lm	0,241 lm	0,591 lm	0,534 lm	0,185 lm

# Light Measurement Report

Print date: 14-4-2025

Measurement date and time: 14-4-2025 14:59:20 – Measurement no. VFR-250414-0761-MS

Measurement tracking No. and Link: [VT250414-000886](#)

Operator:



## Outdoor Light Planning

### Lumen per Zone

Zone (γ)	Lumen	% Total
0-10°	{LUM00-10} lm	#VALUE!
10-20°	{LUM10-20} lm	#VALUE!
20-30°	{LUM20-30} lm	#VALUE!
30-40°	{LUM30-40} lm	#VALUE!
40-50°	{LUM40-50} lm	#VALUE!
50-60°	{LUM50-60} lm	#VALUE!
60-70°	{LUM60-70} lm	#VALUE!
70-80°	{LUM70-80} lm	#VALUE!
80-90°	{LUM80-90} lm	#VALUE!
90-100°	{LUM90-100} lm	#VALUE!
100-110°	{LUM100-110} lm	#VALUE!
110-120°	{LUM110-120} lm	#VALUE!
120-130°	{LUM120-130} lm	#VALUE!
130-140°	{LUM130-140} lm	#VALUE!
140-150°	{LUM140-150} lm	#VALUE!
150-160°	{LUM150-160} lm	#VALUE!
160-170°	{LUM160-170} lm	#VALUE!
170-180°	{LUM170-180} lm	#VALUE!
Total	0 lm	#VALUE!

### Intensity peaks

Max intensity	{PEAK} cd
Intensity, 90°	{INT90} cd
Intensity, 0°	{INT0} cd

### Zonal Lumen summary

Zone (γ)	Lumen	% Total
0-30°	{LUM00-30} lm	#VALUE!
0-40°	{LUM00-40} lm	#VALUE!
0-60°	{LUM00-60} lm	#VALUE!
60-90°	{LUM60-90} lm	#VALUE!
70-100°	{LUM70-100} lm	#VALUE!
90-120°	{LUM90-120} lm	#VALUE!
0-90°	{LUM00-90} lm	#VALUE!
90-180°	{LUM90-180} lm	#VALUE!
0-180°	{LUM00-180} lm	#VALUE!

### BUG rating

	Lumen	% Total
<b>Forward light</b>		
Low(0-30°)	{BUG0} lm	#VALUE!
Medium(30-60°)	{BUG1} lm	#VALUE!
High(60-80°)	{BUG2} lm	#VALUE!
Very high(80-90°)	{BUG3} lm	#VALUE!

### Back light


Low(0-30°)	{BUG4} lm	#VALUE!
Medium(30-60°)	{BUG5} lm	#VALUE!
High(60-80°)	{BUG6} lm	#VALUE!
Very high(80-90°)	{BUG7} lm	#VALUE!

### Uplight

Low(90-100°)	{BUG8} lm	#VALUE!
High(100-180°)	{BUG9} lm	#VALUE!

## IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B3 U1 G0



# Light Measurement Report

Print date: 14-4-2025

Measurement date and time: 14-4-2025 14:59:20 – Measurement no. VFR-250414-0761-MS

Measurement tracking No. and Link: [VT250414-000886](#)

Operator:




## Power Details

### Input Power

Power feed to light source	28,3 W
Frequency of input power	50 Hz
RMS Input voltage feed, $V_{RMS}$	230 V
RMS Input current feed, $I_{RMS}$	0,126 A
Volt-Ampere or apparent power = $V_{RMS} * I_{RMS}$	29,05 VA
Displacement factor of AC power feed	0,98
Power factor of AC current feed	0,97
Total harmonic distortion of the current	6,88%
Total harmonic distortion of the voltage	0,07%

### Input Power Curve



### Efficiency

Radiated power efficiency	27,3%
Lumen efficiency	84 lm/W

## Stabilization Details

### Warmup Conditions

Stable period	15 min
Stable change max	2,0%
Minimum time	15 min

### Color Temperature Change

CCT start	3001 K
CCT shift	-1 K
CCT end	3000 K


### Warmup Result

Total warmup time	Lamp stabilized in 15 min 2 sec
Warmup variation	-0,6%

### Output Change

Output start	2379 lm
Output change	-13 lm
Output end	2367 lm

### Stabilization Curve



# Light Measurement Report

Print date: 14-4-2025

Measurement date and time: 14-4-2025 14:59:20 – Measurement no. VFR-250414-0761-MS

Measurement tracking No. and Link: [VT250414-000886](https://www.viso-systems.com/VT250414-000886)

Operator:



## Flicker /TLA details

Flicker Meter Type: Viso Systems LabFlicker  
 Frequency of input power: 50 Hz  
 Flicker/TLA sample rate: 20000 samples/s

**Measurement time**  
 PstLM: 180 sec  
 All other indices: 1,2 sec

### Flicker indices according to Illuminating Engineering Society (IES)

Flicker frequency: 99,5 Hz  
 Percent Flicker: 0,41 %  
 Flicker index: 0

### Flicker indices according to California Energy Commission (CEC) 2016b

JA8/10 40 Hz: 0,02 %  
 JA8/10 90 Hz: 0,03 %  
 JA8/10 200 Hz: 0,41 %  
 JA8/10 400 Hz: 0,41 %  
 JA8/10 1000 Hz: 0,41 %


### TLA indices (re IEC TR 61547-1, IEC 61000-3-3 and IEC 61000-4-15)

PstLM value (F < 80 Hz): 0,02  
 SVM value (80 < F < 2000 Hz): 0,01

### Flicker indices according to Lighting Research Center (2015)

Perception metric, Assist Mp: 0,01

### Flicker frame (frame of one flicker period in time domain)



### Flicker FFT (flicker curve in frequency domain)



### IEEE 1789 Frequency/modulation plot

