

Light Measurement Report

Print date: 7-1-2025

Measurement date and time: 7-1-2025 16:44:22 – Measurement no. VFR-250107-2773-MS

Measurement tracking No. and Link: [VT250107-004160](https://www.viso-systems.com/VT250107-004160)

Operator:



Laboratory and Equipment

Laboratory Owner and Location
Goniospectrometer System and Type
Sensor Name, Calibr. Date and Serial No.
Spectrometer Manufacturer and Model

Viso Systems, Copenhagen V, Denmark
LabSpion – Type C, horizontal
LabSensor Model2 – 11-1-2024 – 3130191315
Ibsen Photonics, Denmark – Freedom VIS (Custom Viso)

Measurement Conditions

Number of C-planes and Resolution
 γ (gamma)-Resolution
Test Distance
Input Power, Power and Displ. Factors
Input RMS Voltage and Current
Frequency of Input Power
Warm-up Time and Variation

72 planes – 5°
5°
2,00 m
10,8 W – PF 0,92 – DPF 1,0
230 V – 0,051 A
50 Hz
Lamp stabilized in 15 min 2 sec – 2,0%

Tested Light Source



Product Name
Item No. and Manufacturer
Product Description (line 1)

801304-4000K
801304-4000K – Dutchfulfillment
LED AR111 | GU10 | SPOT | 24° | 12W | WIT

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)
Efficiency
Peak Intensity and Beam Angle
Correlated Color Temperature, Target/Measured
Color Rendering Index
Color Rendering TM30-18
Color Shift, CIE duv and MacAdam Steps
Flicker

922 lm – 0,12% / 99,88%
85 lm/W
1860 cd – 27,6°
CCT = 4000 K / 4152 K
CRI 82,5
 R_f 84,1 – R_g 96,6
Duv 0,0025 – SDCM 3,6
SVM 0,17 – PstLM 0,05



Light Measurement Report

Print date: 7-1-2025

Measurement date and time: 7-1-2025 16:44:22 – Measurement no. VFR-250107-2773-MS


Measurement tracking No. and Link: [VT250107-004160](#)

Operator:



Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	922 lm
Lumen Up% / Down%	0,12% / 99,88%
Peak Intensity	1860 cd
Beam Angle (50%)	27,6°
Beam Angle (90%)	27,6°
Beam Angle (10%)	27,6°

Cut-off Angle

Average 2,5%	130,6°
--------------	--------

Field Angle

Average 10%	68,1°
-------------	-------


Intensity Ratio

In 120° cone	94,2%
In 90° cone	76,4%

C000-C180

C090-C270

Linear distribution diagram - Intensity (candela) vs γ -angle



Light Measurement Report

Print date: 7-1-2025


Measurement date and time: 7-1-2025 16:44:22 – Measurement no. VFR-250107-2773-MS

Measurement tracking No. and Link: [VT250107-004160](#)

Operator:



Iso-intensity Diagram (Iso-candela)




90 %	1674,4 cd
80 %	1488,4 cd
70 %	1302,3 cd
60 %	1116,3 cd
50 %	930,2 cd
40 %	744,2 cd
30 %	558,1 cd
20 %	372,1 cd
10 %	186,0 cd

Peak intensity: 1860,5 cd

Number of c-planes: 72

Iso-illuminance Diagram (Iso-lux)



50,0 %	103,4 lx
30,0 %	62,0 lx
10,0 %	20,7 lx
5,0 %	10,3 lx
3,0 %	6,2 lx

Peak illuminance: 206,7 lx

Mounting height: 3,0 m

Number of c-planes: 72

Light Measurement Report

Print date: 7-1-2025

Measurement date and time: 7-1-2025 16:44:22 – Measurement no. VFR-250107-2773-MS

Measurement tracking No. and Link: [VT250107-004160](#)

Operator:




Color details


Correlated Color Temperature, Target CCT = 4000 K
 Correlated Color Temperature, Measured CCT = 4152 K
 Color Rendering Index CRI 82,5
 Color Rendering Index, R9 (red component) R9 = 7,0
 Color Rendering TM30-18 R_f 84,1 – R_g 96,6
 Color Quality Scale CQS = 82,7

MacAdam Steps SDCM = 3,6
 Color coordinates CIE 1931 (x;y) = (0,381;0,377)
 Color coordinate CIEs 1960 (u;v) = (0,225;0,334)
 Color deviation from BBL Duv = 0,0025
 Color coordinate CIEs 1976 (CIELUV) (u';v') = (0,225;0,502)


CIE 1931



CIE 1931 – zoomed on Planckian locus




Color Rendering Index per reference color (CIE 1995)




CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
80,7	87,1	92,9	83,3	80,9	82,9	86,9	65,7	7,0	70,1	82,9	61,7	82,1	96,1	73,3

Spectral power distribution (SPD) / W/nm – 0-100%




TM30-18 Rf-values per hue bin



TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
80,6	83,4	76,7	86,0	89,2	92,6	92,3	89,9	88,8	79,6	78,4	83,4	86,6	86,1	78,4	78,2

Color Quality Scale by reference color



CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
81,6	98,4	79,1	77,8	82,8	83,8	85,3	89,4	97,3	87,7	85,4	84,4	83,9	71,2	75,0

Light Measurement Report

Print date: 7-1-2025


Measurement date and time: 7-1-2025 16:44:22 – Measurement no. VFR-250107-2773-MS

Measurement tracking No. and Link: [VT250107-004160](https://www.viso-systems.com/VT250107-004160)

Operator:



Beam Details



Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3,3	6,6	9,8	13,1	16,4	19,7	23	26,2	29,5	32,8	36,1	39,4	42,7	45,9	49,2	52,5	55,8	59,1	62,3	65,6	ft
1860	465	207	116	74	52	38	29	23	19	15	13	11	9	8	7	6	6	5	5	lux
172,8	43,2	19,2	10,8	6,9	4,8	3,5	2,7	2,1	1,7	1,4	1,2	1	0,9	0,8	0,7	0,6	0,5	0,5	0,4	fc

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
1860	1860	1777	1647	1506	1300	1093	916	755	604	517	429	368	320	275	242	208	186	171	157	cd
100%	100%	96%	89%	81%	70%	59%	49%	41%	32%	28%	23%	20%	17%	15%	13%	11%	10%	9%	8%	of 0°val

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
1860	1860	1777	1647	1506	1300	1093	916	755	604	517	429	368	320	275	242	208	186	171	157	cd
100%	100%	96%	89%	81%	70%	59%	49%	41%	32%	28%	23%	20%	17%	15%	13%	11%	10%	9%	8%	of 0°val

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
1860	1860	1777	1647	1506	1300	1093	916	755	604	517	429	368	320	275	242	208	186	171	157	cd
100%	100%	96%	89%	81%	70%	59%	49%	41%	32%	28%	23%	20%	17%	15%	13%	11%	10%	9%	8%	of 0°val

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
1860	1860	1777	1647	1506	1300	1093	916	755	604	517	429	368	320	275	242	208	186	171	157	cd
100%	100%	96%	89%	81%	70%	59%	49%	41%	32%	28%	23%	20%	17%	15%	13%	11%	10%	9%	8%	of 0°val

Light Measurement Report

Print date: 7-1-2025

Measurement date and time: 7-1-2025 16:44:22 – Measurement no. VFR-250107-2773-MS

Measurement tracking No. and Link: [VT250107-004160](#)

Operator:



Light Planning – UGR table

Uncorrected, comprehensive UGR table according to 117-1995

Reflectances		70	70	50	50	30	70	70	50	50	30
	ρ Ceiling	70	70	50	50	30	70	70	50	50	30
	ρ Walls	50	30	50	30	30	50	30	50	30	30
	ρ Floor	20	20	20	20	20	20	20	20	20	20
Room size		Viewed Crosswise					Viewed Endwise				
H = mounting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	Y										
2H	2H	22,3	23,1	22,5	23,4	23,6	22,3	23,1	22,5	23,4	23,6
	3H	22,5	23,4	22,9	23,6	23,8	22,5	23,4	22,9	23,6	23,8
	4H	22,5	23,3	22,9	23,6	23,8	22,5	23,3	22,9	23,6	23,8
	6H	22,5	23,2	22,8	23,5	23,8	22,5	23,2	22,8	23,5	23,8
	8H	22,4	23,1	22,7	23,4	23,8	22,4	23,1	22,7	23,4	23,8
	12H	22,3	23,0	22,7	23,4	23,8	22,3	23,0	22,7	23,4	23,8
4H	2H	22,5	23,4	22,9	23,6	23,9	22,5	23,4	22,9	23,6	23,9
	3H	22,9	23,6	23,3	23,9	24,4	22,9	23,6	23,3	23,9	24,4
	4H	22,8	23,4	23,2	23,8	24,4	22,8	23,4	23,2	23,8	24,4
	6H	22,7	23,4	23,2	23,7	24,1	22,7	23,4	23,2	23,7	24,1
	8H	22,7	23,2	23,2	23,6	24,0	22,7	23,2	23,2	23,6	24,0
	12H	22,6	23,1	23,1	23,5	24,0	22,6	23,1	23,1	23,5	24,0
8H	4H	22,7	23,3	23,2	23,6	24,0	22,7	23,3	23,2	23,6	24,0
	6H	22,6	23,0	23,1	23,5	24,0	22,6	23,0	23,1	23,5	24,0
	8H	22,6	23,0	23,1	23,5	24,1	22,6	23,0	23,1	23,5	24,1
	12H	22,6	22,8	23,2	23,4	24,0	22,6	22,8	23,2	23,4	24,0
12H	4H	22,6	23,1	23,1	23,5	24,0	22,6	23,1	23,1	23,5	24,0
	6H	22,6	23,0	23,1	23,5	24,1	22,6	23,0	23,1	23,5	24,1
	8H	22,6	22,8	23,2	23,4	24,0	22,6	22,8	23,2	23,4	24,0

Variations with the observer position for the luminaire spacings, S:

S = 1.0H	0,3 / -0,2	0,3 / -0,2
S = 1.5H	1,0 / -1,6	1,0 / -1,6
S = 2.0H	2,3 / -5,1	2,3 / -5,1

Coefficients of Utilization

Ceiling reflectance	80	70	50	30	10	0
Wall reflectance	70 50 30	10 70 50	30 10 50	30 10 50	30 10 50	30 10 0
Floor reflectance	20 20 20	20 20 20	20 20 20	20 20 20	20 20 20	20 20 0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumen delivered to the task surface					
0	119 119 119	119 116 116	116 116 111	111 111 106	106 106 102	102 102 100
1	113 109 106	104 110 107	105 102 103	101 99 99	98 96 96	94 93 91
2	106 100 95	91 103 98	94 90 95	91 88 92	89 86 89	87 85 83
3	99 92 86	82 97 90	85 81 88	83 80 85	81 78 83	80 77 75
4	94 85 79	74 92 84	78 73 81	76 72 79	75 71 77	74 71 69
5	88 79 72	67 87 78	72 67 76	71 66 74	70 66 73	69 65 64
6	84 74 67	62 82 73	67 62 71	66 62 70	65 61 68	64 61 59
7	79 69 63	58 78 68	62 58 67	61 57 66	61 57 65	60 57 55
8	76 65 59	54 74 65	58 54 63	58 54 62	57 54 61	57 53 52
9	72 62 55	51 71 61	55 51 60	55 51 59	54 51 58	54 51 49
10	69 59 53	48 68 58	52 48 57	52 48 57	52 48 56	51 48 47

Light Measurement Report

Print date: 7-1-2025

Measurement date and time: 7-1-2025 16:44:22 – Measurement no. VFR-250107-2773-MS

Measurement tracking No. and Link: [VT250107-004160](#)


Operator:



Luminaire budgetary diagram

Uncorrected, comprehensive UGR table according to 117-1995

LAMPS (number of lamps)



Conditions

H = Room height	Flux = 922 lm				
H _{down} = Lamp distance from ceiling =	0.00 m	Line type	Ceiling reflectance	ρ(%) Wall reflectance	Floor reflectance
H _{work} = Work area height from floor =	0.00 m	-----	70	50	30
E _{work} = Average lux on work area =	100 lx	_____	50	30	20

Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
155 lm	227 lm	157 lm	112 lm	111 lm	106 lm	47,9 lm	4,76 lm	0,199 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0,172 lm	0,149 lm	0,151 lm	0,130 lm	0,136 lm	0,103 lm	0,107 lm	0,087 lm	0,028 lm

Light Measurement Report

Print date: 7-1-2025

Measurement date and time: 7-1-2025 16:44:22 – Measurement no. VFR-250107-2773-MS

Measurement tracking No. and Link: [VT250107-004160](#)

Operator:



Outdoor Light Planning

Lumen per Zone

Zone (γ)	Lumen	% Total
0-10°	155 lm	16,8%
10-20°	227 lm	24,6%
20-30°	157 lm	17,1%
30-40°	112 lm	12,2%
40-50°	111 lm	12,0%
50-60°	106 lm	11,5%
60-70°	48 lm	5,2%
70-80°	5 lm	0,5%
80-90°	0 lm	0,0%
90-100°	0 lm	0,0%
100-110°	0 lm	0,0%
110-120°	0 lm	0,0%
120-130°	0 lm	0,0%
130-140°	0 lm	0,0%
140-150°	0 lm	0,0%
150-160°	0 lm	0,0%
160-170°	0 lm	0,0%
170-180°	0 lm	0,0%
Total	922 lm	100,0%

Intensity peaks

Max intensity	1860 cd
Intensity, 90°	0 cd
Intensity, 0°	1860 cd

Zonal Lumen summary


Zone (γ)	Lumen	% Total
0-30°	540 lm	58,5%
0-40°	652 lm	70,7%
0-60°	868 lm	94,2%
60-90°	53 lm	5,7%
70-100°	5 lm	0,6%
90-120°	0 lm	0,1%
0-90°	921 lm	99,9%
90-180°	1 lm	0,1%
0-180°	922 lm	100,0%

BUG rating

	Lumen	% Total
Forward light		
Low(0-30°)	269 lm	29,2%
Medium(30-60°)	164 lm	17,8%
High(60-80°)	27 lm	2,9%
Very high(80-90°)	0 lm	0,0%
Back light		
Low(0-30°)	269 lm	29,2%
Medium(30-60°)	164 lm	17,8%
High(60-80°)	27 lm	2,9%
Very high(80-90°)	0 lm	0,0%
Uplight		
Low(90-100°)	0 lm	0,0%
High(100-180°)	1 lm	0,1%

IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B1 U1 G0



Light Measurement Report

Print date: 7-1-2025

Measurement date and time: 7-1-2025 16:44:22 – Measurement no. VFR-250107-2773-MS

Measurement tracking No. and Link: [VT250107-004160](#)

Operator:




Power Details


Input Power

Power feed to light source	10,8 W
Frequency of input power	50 Hz
RMS Input voltage feed, V_{RMS}	230 V
RMS Input current feed, I_{RMS}	0,051 A
Volt-Ampere or apparent power = $V_{RMS} * I_{RMS}$	11,75 VA
Displacement factor of AC power feed	1,0
Power factor of AC current feed	0,92
Total harmonic distortion of the current	42,34%
Total harmonic distortion of the voltage	0,06%

Input Power Curve



Efficiency



Stabilization Details

Warmup Conditions

Stable period	15 min
Stable change max	2,0%
Minimum time	15 min

Color Temperature Change

CCT start	3989 K
CCT shift	+11 K
CCT end	4000 K


Warmup Result

Total warmup time	Lamp stabilized in 15 min 2 sec
Warmup variation	-0,4%

Output Change

Output start	926 lm
Output change	-4 lm
Output end	922 lm

Stabilization Curve



Light Measurement Report

Print date: 7-1-2025

Measurement date and time: 7-1-2025 16:44:22 – Measurement no. VFR-250107-2773-MS

Measurement tracking No. and Link: [VT250107-004160](#)

Operator:



Flicker /TLA details

Flicker Meter Type Viso Systems LabFlicker
 Frequency of input power 50 Hz
 Flicker/TLA sample rate 20000 samples/s

Measurement time
 PstLM 180 sec
 All other indices 1,2 sec

Flicker indices according to Illuminating Engineering Society (IES)

Flicker frequency 100 Hz
 Percent Flicker 8,06 %
 Flicker index 0,02

Flicker indices according to California Energy Commission (CEC) 2016b

JA8/10 40 Hz 0,03 %
 JA8/10 90 Hz 0,04 %
 JA8/10 200 Hz 4,51 %
 JA8/10 400 Hz 6,75 %
 JA8/10 1000 Hz 7,83 %


TLA indices (re IEC TR 61547-1, IEC 61000-3-3 and IEC 61000-4-15)

PstLM value (F < 80 Hz) 0,05
 SVM value (80 < F < 2000 Hz) 0,17


Flicker indices according to Lighting Research Center (2015)

Perception metric, Assist Mp 0,02

Flicker frame (frame of one flicker period in time domain)



Flicker FFT (flicker curve in frequency domain)



IEEE 1789 Frequency/modulation plot

