

Light efficiency:



Light quality:



Color temperature:



Output: 3722 lm

Peak: 1787 cd

Power: 24,3 W

PF: 0,96



Tracking number: [VT241001-009669](#)

Product name:

802240-4000K

Item number:


802240-4000K

Date and time:

1-10-2024 10:18:46

Description:

**BACK-LIT LED PANEEL | CUPID |
120X30CM | 25W**




Beam angle **86°**






CIE 1931
x: 0,381
y: 0,377

Spectra





Power






TM-30: 82,6

CRI: 83,2 (R1-R8)



CQS: 83,1



CRI R values, only R1-R8 are used to calculate final CRI value

| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 84,6 | 84,6 | 82,7 | 85,3 | 82,4 | 78,4 | 88,8 | 79,2 | 39,3 | 61,6 | 84,1 | 50,6 | 83,6 | 89,5 | 81,4 |

TM30 C values, 16 binned values out of total of 99 C values

| C1 | C2 | C3 | C4 | C5 | C6 | C7 | C8 | C9 | C10 | C11 | C12 | C13 | C14 | C15 | C16 |
|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 85,2 | 87,5 | 76,3 | 81,5 | 84,1 | 87,1 | 90,3 | 88,8 | 88,1 | 75,9 | 72,3 | 74,6 | 85,1 | 86,7 | 81,5 | 79,8 |

CQS Q values

| Q1 | Q2 | Q3 | Q4 | Q5 | Q6 | Q7 | Q8 | Q9 | Q10 | Q11 | Q12 | Q13 | Q14 | Q15 |
|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 86,3 | 97,0 | 72,2 | 73,9 | 81,6 | 81,4 | 81,7 | 90,4 | 92,3 | 83,5 | 83,8 | 86,3 | 88,6 | 81,8 | 82,8 |







Color parameters


| Color temperature | Color rendering index | Red component | Color fidelity | Color gamut | Color quality scale | Color coordinate cie 1931 | Color coordinate cie 1931 | Color coordinate | Color coordinate | Color deviation from black body |
|-------------------|-----------------------|---------------|----------------|-------------|---------------------|---------------------------|---------------------------|------------------|------------------|---------------------------------|
| CCT | CRI | CRI R9 | TM30 Rf | TM30 Rg | CQS | x | y | u | v | Δuv |
| 4000 K | 83,2 | 39,3 | 82,6 | 100,5 | 83,1 | 0,381 | 0,377 | 0,225 | 0,334 | 0,0024 |

Rf 82,6
Fidelity index Rf

Rg 100,5
Gamut index Rg

| Hue Bin | R _f | Shifts (%) | |
|---------|----------------|------------|------|
| | | Chroma | Hue |
| 1 | 85 | -8% | -3% |
| 2 | 88 | -6% | 4% |
| 3 | 76 | -3% | 12% |
| 4 | 82 | 2% | 12% |
| 5 | 84 | 6% | 8% |
| 6 | 87 | 8% | 0% |
| 7 | 90 | 2% | -6% |
| 8 | 89 | -3% | -6% |
| 9 | 88 | -8% | 0% |
| 10 | 76 | -10% | 11% |
| 11 | 72 | 0% | 19% |
| 12 | 75 | 6% | 13% |
| 13 | 85 | 10% | 1% |
| 14 | 87 | 10% | -1% |
| 15 | 81 | 5% | -13% |
| 16 | 80 | 0% | -13% |





Beam intensities from 1-20m

| 1m | 2m | 3m | 4m | 5m | 6m | 7m | 8m | 9m | 10m | 11m | 12m | 13m | 14m | 15m | 16m | 17m | 18m | 19m | 20m |
|----------|---------|---------|---------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 3,3ft | 6,6ft | 9,8ft | 13,1ft | 16,4ft | 19,7ft | 23ft | 26,2ft | 29,5ft | 32,8ft | 36,1ft | 39,4ft | 42,7ft | 45,9ft | 49,2ft | 52,5ft | 55,8ft | 59,1ft | 62,3ft | 65,6ft |
| 1787lx | 447lx | 199lx | 112lx | 71lx | 50lx | 36lx | 28lx | 22lx | 18lx | 15lx | 12lx | 11lx | 9lx | 8lx | 7lx | 6lx | 6lx | 5lx | 4lx |
| 166,1fcd | 41,5fcd | 18,5fcd | 10,4fcd | 6,6fcd | 4,6fcd | 3,4fcd | 2,6fcd | 2,1fcd | 1,7fcd | 1,4fcd | 1,2fcd | 1fcd | 0,8fcd | 0,7fcd | 0,6fcd | 0,6fcd | 0,5fcd | 0,5fcd | 0,4fcd |

Intensities in 0° c-plane

| 0° | 5° | 10° | 15° | 20° | 25° | 30° | 35° | 40° | 45° | 50° | 55° | 60° | 65° | 70° | 75° | 80° | 85° | 90° | 95° |
|------|------|------|------|------|------|------|------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 1787 | 1786 | 1760 | 1722 | 1669 | 1598 | 1494 | 1319 | 1046 | 796 | 609 | 436 | 313 | 247 | 193 | 142 | 105 | 60 | 15 | 5 |
| 100% | 100% | 98% | 96% | 93% | 89% | 84% | 74% | 58% | 45% | 34% | 24% | 18% | 14% | 11% | 8% | 6% | 3% | 1% | 0% |

Intensities in 90° c-plane

| 0° | 5° | 10° | 15° | 20° | 25° | 30° | 35° | 40° | 45° | 50° | 55° | 60° | 65° | 70° | 75° | 80° | 85° | 90° | 95° |
|------|------|------|------|------|------|------|------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 1787 | 1786 | 1760 | 1722 | 1669 | 1598 | 1494 | 1319 | 1046 | 796 | 609 | 436 | 313 | 247 | 193 | 142 | 105 | 60 | 15 | 5 |
| 100% | 100% | 98% | 96% | 93% | 89% | 84% | 74% | 58% | 45% | 34% | 24% | 18% | 14% | 11% | 8% | 6% | 3% | 1% | 0% |

Intensities in 180° c-plane


| 0° | 5° | 10° | 15° | 20° | 25° | 30° | 35° | 40° | 45° | 50° | 55° | 60° | 65° | 70° | 75° | 80° | 85° | 90° | 95° |
|------|------|------|------|------|------|------|------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 1787 | 1786 | 1760 | 1722 | 1669 | 1598 | 1494 | 1319 | 1046 | 796 | 609 | 436 | 313 | 247 | 193 | 142 | 105 | 60 | 15 | 5 |
| 100% | 100% | 98% | 96% | 93% | 89% | 84% | 74% | 58% | 45% | 34% | 24% | 18% | 14% | 11% | 8% | 6% | 3% | 1% | 0% |

Intensities in 270° c-plane

| 0° | 5° | 10° | 15° | 20° | 25° | 30° | 35° | 40° | 45° | 50° | 55° | 60° | 65° | 70° | 75° | 80° | 85° | 90° | 95° |
|------|------|------|------|------|------|------|------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 1787 | 1786 | 1760 | 1722 | 1669 | 1598 | 1494 | 1319 | 1046 | 796 | 609 | 436 | 313 | 247 | 193 | 142 | 105 | 60 | 15 | 5 |
| 100% | 100% | 98% | 96% | 93% | 89% | 84% | 74% | 58% | 45% | 34% | 24% | 18% | 14% | 11% | 8% | 6% | 3% | 1% | 0% |

| Beam angle 50% | Field angle 10% | Cutoff angle 2,5% | Intensity ratio in 120° cone | Intensity ratio in 90° cone |
|----------------|-----------------|-------------------|------------------------------|-----------------------------|
| 86° | 142,7° | 173,2° | 86,4% | 68,1% |

iso-candela diagram




| | |
|-----|---------|
| 10% | 179 cd |
| 20% | 357 cd |
| 30% | 536 cd |
| 40% | 715 cd |
| 50% | 894 cd |
| 60% | 1072 cd |
| 70% | 1251 cd |
| 80% | 1430 cd |
| 90% | 1609 cd |

Conditions:

Number of c-planes: 12

Candela at center: 1787 cd

iso-lux diagram



Mounting height: 10 meters (33 feet)

| | |
|-----|----------|
| 3% | 0,536 lx |
| 5% | 0,894 lx |
| 10% | 1,79 lx |
| 30% | 5,36 lx |
| 50% | 8,94 lx |

Conditions:

Number of c-planes: 12

Lux at center: 17,9 lx

Lux distribution on a surface when lamp is mounted at 10 meters from the surface.

Glare evaluation according to UGR


| | | | | | | | | | | | |
|--|--|------|------|------|------|---|------|------|------|------|------|
| p Ceiling | 70 | 70 | 50 | 50 | 30 | 70 | 70 | 50 | 50 | 30 | |
| p Walls | 50 | 30 | 50 | 30 | 30 | 50 | 30 | 50 | 30 | 30 | |
| p Floor | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | |
| Room size X Y | Viewing direction at right angles to lamp axis | | | | | Viewing direction parallel to lamp axis | | | | | |
| 2H | 2H | 15,2 | 16,2 | 15,4 | 16,5 | 16,7 | 15,1 | 16,1 | 15,3 | 16,4 | 16,6 |
| | 3H | 15,9 | 17,0 | 16,4 | 17,3 | 17,5 | 15,8 | 16,9 | 16,3 | 17,2 | 17,4 |
| | 4H | 16,4 | 17,5 | 16,8 | 17,7 | 18,0 | 16,3 | 17,3 | 16,7 | 17,6 | 17,9 |
| | 6H | 16,9 | 17,9 | 17,3 | 18,2 | 18,5 | 16,8 | 17,7 | 17,1 | 18,0 | 18,4 |
| | 8H | 17,1 | 18,0 | 17,5 | 18,4 | 18,8 | 16,9 | 17,8 | 17,3 | 18,2 | 18,6 |
| | 12H | 17,3 | 18,2 | 17,7 | 18,5 | 19,0 | 17,1 | 17,9 | 17,5 | 18,3 | 18,7 |
| 4H | 2H | 15,4 | 16,4 | 15,8 | 16,7 | 17,0 | 15,3 | 16,4 | 15,7 | 16,6 | 16,9 |
| | 3H | 16,6 | 17,4 | 16,9 | 17,8 | 18,2 | 16,5 | 17,3 | 16,8 | 17,7 | 18,1 |
| | 4H | 17,1 | 17,9 | 17,6 | 18,3 | 18,9 | 17,0 | 17,8 | 17,4 | 18,2 | 18,7 |
| | 6H | 17,7 | 18,5 | 18,2 | 18,9 | 19,2 | 17,6 | 18,3 | 18,1 | 18,7 | 19,1 |
| | 8H | 18,0 | 18,7 | 18,5 | 19,1 | 19,5 | 17,8 | 18,5 | 18,3 | 18,9 | 19,3 |
| | 12H | 18,3 | 18,8 | 18,8 | 19,3 | 19,8 | 18,0 | 18,6 | 18,5 | 19,0 | 19,5 |
| 8H | 4H | 17,3 | 18,0 | 17,8 | 18,4 | 18,8 | 17,2 | 17,9 | 17,7 | 18,3 | 18,7 |
| | 6H | 18,2 | 18,7 | 18,7 | 19,1 | 19,7 | 18,0 | 18,5 | 18,5 | 19,0 | 19,5 |
| | 8H | 18,6 | 19,0 | 19,1 | 19,6 | 20,2 | 18,4 | 18,8 | 18,9 | 19,4 | 20,0 |
| | 12H | 18,9 | 19,3 | 19,5 | 19,8 | 20,5 | 18,7 | 19,1 | 19,3 | 19,6 | 20,2 |
| 12H | 4H | 17,3 | 17,9 | 17,8 | 18,4 | 18,8 | 17,2 | 17,8 | 17,7 | 18,2 | 18,7 |
| | 6H | 18,3 | 18,7 | 18,8 | 19,2 | 19,9 | 18,1 | 18,5 | 18,6 | 19,1 | 19,7 |
| | 8H | 18,7 | 19,1 | 19,3 | 19,6 | 20,2 | 18,5 | 18,9 | 19,1 | 19,4 | 20,0 |
| Variation of the observer position for the luminaire distance S | | | | | | | | | | | |
| S = 1.0H | 0,1 / -0,3 | | | | | 0,2 / -0,3 | | | | | |
| S = 1.5H | 0,5 / -0,5 | | | | | 0,5 / -0,6 | | | | | |
| S = 2.0H | 1,1 / -0,8 | | | | | 1,1 / -0,8 | | | | | |
| CIE 117-1995. Corrected glare indices referring to 3722 lm total luminous flux | | | | | | | | | | | |

Coefficients of Utilization

| Ceiling reflectance | 80 | | | | 70 | | | | 50 | | | 30 | | | 10 | | | 0 | | | |
|---------------------|---|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|---|
| Wall reflectance | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 | | | |
| Floor reflectance | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 0 |
| RCR | (RCR: Room Cavity Ratio) | | | | | | | | | | | | | | | | | | | | |
| | Room Values are expressed as percentage of Lumens delivered to the task surface | | | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 110 | 110 | 110 | 106 | 106 | 106 | 101 | 101 | 101 | 99 | | | |
| 1 | 110 | 106 | 102 | 99 | 107 | 103 | 100 | 97 | 99 | 96 | 94 | 95 | 93 | 91 | 91 | 89 | 88 | 86 | | | |
| 2 | 101 | 94 | 88 | 83 | 99 | 92 | 87 | 82 | 89 | 84 | 80 | 85 | 82 | 78 | 82 | 79 | 76 | 74 | | | |
| 3 | 94 | 84 | 77 | 72 | 91 | 83 | 76 | 71 | 80 | 74 | 70 | 77 | 72 | 68 | 74 | 70 | 67 | 65 | | | |
| 4 | 87 | 76 | 68 | 62 | 85 | 75 | 68 | 62 | 72 | 66 | 61 | 70 | 64 | 60 | 68 | 63 | 59 | 57 | | | |
| 5 | 81 | 69 | 61 | 55 | 78 | 68 | 60 | 55 | 66 | 59 | 54 | 64 | 58 | 53 | 62 | 57 | 53 | 51 | | | |
| 6 | 75 | 63 | 55 | 49 | 73 | 62 | 54 | 49 | 60 | 53 | 48 | 58 | 52 | 48 | 57 | 51 | 47 | 45 | | | |
| 7 | 70 | 58 | 50 | 44 | 68 | 57 | 49 | 44 | 55 | 48 | 43 | 54 | 48 | 43 | 52 | 47 | 43 | 41 | | | |
| 8 | 65 | 53 | 45 | 40 | 64 | 52 | 45 | 40 | 51 | 44 | 39 | 50 | 44 | 39 | 48 | 43 | 39 | 37 | | | |
| 9 | 61 | 49 | 41 | 36 | 60 | 48 | 41 | 36 | 47 | 41 | 36 | 46 | 40 | 36 | 45 | 39 | 35 | 34 | | | |
| 10 | 58 | 45 | 38 | 33 | 56 | 45 | 38 | 33 | 44 | 37 | 33 | 43 | 37 | 33 | 42 | 36 | 33 | 31 | | | |

LAMPS (number of lamps)

Luminaire budgetary diagram




Zonal Lumen Summary

| | | | | | | | | |
|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| 0°-10° | 10°-20° | 20°-30° | 30°-40° | 40°-50° | 50°-60° | 60°-70° | 70°-80° | 80°-90° |
| {LUM0-10} | 486 lm | 734 lm | 808 lm | 622 lm | 398 lm | 247 lm | 154 lm | 64,8 lm |
| 90°-100° | 100°-110° | 110°-120° | 120°-130° | 130°-140° | 140°-150° | 150°-160° | 160°-170° | 170°-180° |
| 8,19 lm | 5,19 lm | 5,54 lm | 5,54 lm | 5,44 lm | 4,55 lm | 3,61 lm | 2,17 lm | 0,781 lm |


LCS table

| BUG rating: | B2 U2 G1 | |
|----------------------|----------|----------|
| Forward light | Lumens | Lumens % |
| Low(0-30): | 694,2 | 18,6% |
| Medium(30-60): | 913,9 | 24,6% |
| High(60-80): | 200,2 | 5,4% |
| Very high(80-90): | 32,4 | 0,9% |
| Back light | | |
| Low(0-30): | 694,2 | 18,6% |
| Medium(30-60): | 913,9 | 24,6% |
| High(60-80): | 200,2 | 5,4% |
| Very high(80-90): | 32,4 | 0,9% |
| Uplight | | |
| Low(90-100): | 8,2 | 0,2% |
| High(100-180): | 32,8 | 0,9% |

LCS graph



Warmup curve



Warmup result

| | |
|-------------------------|--|
| Warmup time: | Lamp stabilized in 15 min 1 sec |
| Warmup variation | +0,8% |

Warmup conditions

| | |
|---------------------------|---------------|
| Stable period: | 15 min |
| Stable change max: | 2,0% |
| Minimum time: | 15 min |

Color temperature change

| CCT start | CCT change | CCT end |
|-----------|------------|---------|
| 3994 K | +6 K | 4000 K |


Output change

| Output start | Output change | Output end |
|--------------|---------------|------------|
| 3692 lm | +30 lm | 3722 lm |

Flicker curve (complete sampled flicker signal)



Flicker frame (frame of one flicker period)



Flicker FFT (frequency scope of flicker curve)



Flicker results:

| Flicker frequency: | | 91,32 Hz | |
|-----------------------|--------|---------------|--------|
| Flicker index: | 0 | JA8/10 40Hz | 0,02 % |
| Flicker percentage: | 0,12 % | JA8/10 90Hz | 0,03 % |
| SVM: (Visual flicker) | 0 | JA8/10 200Hz | 0,09 % |
| PstLM | 0,01 | JA8/10 400Hz | 0,1 % |
| Mp | 0,01 | JA8/10 1000Hz | 0,11 % |

Flicker conditions:

| | |
|--------------|----------------------|
| Sample rate: | 20000 samples/second |
|--------------|----------------------|