

Light Measurement Report

Print date: 10-2-2025

Measurement date and time: 10-2-2025 15:46:19 – Measurement no. VFR-250210-3331-MS

Measurement tracking No. and Link: [VT250210-007947](#)

Operator:



Laboratory and Equipment

Laboratory Owner and Location

Goniospectrometer System and Type

Sensor Name, Calibr. Date and Serial No.

Spectrometer Manufacturer and Model

Viso Systems, Copenhagen V, Denmark

LabSpion – Type C, horizontal

LabSensor Model2 – 11-1-2024 – 3130191315

Ibsen Photonics, Denmark – Freedom VIS (Custom Viso)

Measurement Conditions

Number of C-planes and Resolution

γ (gamma)-Resolution

Test Distance

Input Power, Power and Displ. Factors

Input RMS Voltage and Current

Frequency of Input Power

Warm-up Time and Variation

12 planes – 30°

5°

4,23 m

18,0 W – PF 0,93 – DPF 0,96

230 V – 0,084 A

50 Hz

Lamp stabilized in 15 min 1 sec – 2,0%

Tested Light Source

Product Name

Item No. and Manufacturer

Product Description (line 1)

DZ-M150-5000K-18W

DZ-M150-5000K-18W – Dutchfulfillment

LED DOWNLIGHT | RAINBOW | 18/25W | CCT SWITCH

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)

Efficiency

Peak Intensity and Beam Angle

Correlated Color Temperature, Target/Measured

Color Rendering Index

Color Rendering TM30-18

Color Shift, CIE duv and MacAdam Steps

Flicker

1745 lm – 0,31% / 99,69%

97 lm/W

611 cd – 111,5°



CCT = 5000 K / 4555 K

CRI 84,3

R_f 83,9 – R_g 92,8

Duv 0,0040 – SDCM 9,0

SVM 1,1 – PstLM 0,16



Light Measurement Report

Print date: 10-2-2025

Measurement date and time: 10-2-2025 15:46:19 – Measurement no. VFR-250210-3331-MS


Measurement tracking No. and Link: [VT250210-007947](#)

Operator:



Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	1745 lm
Lumen Up% / Down%	0,31% / 99,69%
Peak Intensity	611 cd
Beam Angle (50%)	111,5°
Beam Angle (90%)	111,6°
Beam Angle (10%)	111,5°

Cut-off Angle

Average 2,5%	175,5°
--------------	--------

Field Angle

Average 10%	163,2°
-------------	--------


Intensity Ratio

In 120° cone	78,0%
In 90° cone	53,2%

C000-C180

C090-C270

Linear distribution diagram - Intensity (candela) vs γ-angle




Light Measurement Report


Print date: 10-2-2025
Measurement date and time: 10-2-2025 15:46:19 – Measurement no. VFR-250210-3331-MS
Measurement tracking No. and Link: [VT250210-007947](#)
Operator:



Iso-intensity Diagram (Iso-candela)



Iso-illuminance Diagram (Iso-lux)



Light Measurement Report

Print date: 10-2-2025

Measurement date and time: 10-2-2025 15:46:19 – Measurement no. VFR-250210-3331-MS

Measurement tracking No. and Link: [VT250210-007947](#)

Operator:




Color details


Correlated Color Temperature, Target CCT = 5000 K
Correlated Color Temperature, Measured CCT = 4555 K
Color Rendering Index CRI 84,3
Color Rendering Index, R9 (red component) R9 = 12,3
Color Rendering TM30-18 R_f 83,9 – R_g 92,8
Color Quality Scale CQS = 83,2

MacAdam Steps
Color coordinates CIE 1931 (x;y) = (0,345;0,352)
Color coordinate CIEs 1960 (u;v) = (0,211;0,323)
Color deviation from BBL Duv = 0,0040
Color coordinate CIEs 1976 (CIELUV) (u';v') = (0,211;0,485)


CIE 1931



CIE 1931 – zoomed on Planckian locus




Color Rendering Index per reference color (CIE 1995)




CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
82,9	92,1	96,2	80,7	82,0	88,0	86,2	66,4	12,3	80,4	80,3	58,2	85,9	98,4	75,6

Spectral power distribution (SPD) / W/nm – 0-100%




TM30-18 Rf-values per hue bin



TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
77,3	86,0	83,3	89,2	90,3	93,2	88,3	86,7	82,0	75,9	79,6	88,4	84,8	85,4	74,1	78,5

Color Quality Scale by reference color



CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
79,2	95,8	83,7	76,4	79,1	80,4	84,5	89,7	97,0	93,4	89,5	87,6	86,0	73,5	76,4

Light Measurement Report

Print date: 10-2-2025


Measurement date and time: 10-2-2025 15:46:19 – Measurement no. VFR-250210-3331-MS

Measurement tracking No. and Link: [VT250210-007947](#)

Operator:



Beam Details



Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3,3	6,6	9,8	13,1	16,4	19,7	23	26,2	29,5	32,8	36,1	39,4	42,7	45,9	49,2	52,5	55,8	59,1	62,3	65,6	ft
611	153	68	38	24	17	12	10	8	6	5	4	4	3	3	2	2	2	2	2	lux
56,7	14,2	6,3	3,5	2,3	1,6	1,2	0,9	0,7	0,6	0,5	0,4	0,3	0,3	0,3	0,2	0,2	0,2	0,2	0,1	fc

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
611	608	599	584	565	541	512	478	441	401	358	312	264	216	167	120	75	34	6	1	cd
100%	100%	98%	96%	92%	89%	84%	78%	72%	66%	59%	51%	43%	35%	27%	20%	12%	5%	1%	0%	of 0°val

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
611	608	599	585	565	541	512	479	442	402	359	313	266	217	169	121	76	34	8	1	cd
100%	100%	98%	96%	93%	89%	84%	78%	72%	66%	59%	51%	43%	36%	28%	20%	12%	6%	1%	0%	of 0°val

Intensities in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
611	608	599	584	565	541	512	478	441	401	358	312	264	216	167	120	75	34	6	1	cd
100%	100%	98%	96%	92%	89%	84%	78%	72%	66%	59%	51%	43%	35%	27%	20%	12%	5%	1%	0%	of 0°val

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
611	608	599	585	565	541	512	479	442	402	359	313	266	217	169	121	76	34	8	1	cd
100%	100%	98%	96%	93%	89%	84%	78%	72%	66%	59%	51%	43%	36%	28%	20%	12%	6%	1%	0%	of 0°val

Light Measurement Report

Print date: 10-2-2025

Measurement date and time: 10-2-2025 15:46:19 – Measurement no. VFR-250210-3331-MS

Measurement tracking No. and Link: [VT250210-007947](#)

Operator:



Light Planning – UGR table

Uncorrected, comprehensive UGR table according to 117-1995

Reflectances											
	p Ceiling	70	70	50	50	30	70	70	50	50	30
	p Walls	50	30	50	30	30	50	30	50	30	30
	p Floor	20	20	20	20	20	20	20	20	20	20
Room size		Viewed Crosswise					Viewed Endwise				
H = mounting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	Y										
2H	2H	20,7	21,9	20,9	22,2	22,5	20,7	21,9	21,0	22,3	22,5
	3H	22,1	23,4	22,5	23,7	23,9	22,2	23,4	22,6	23,7	23,9
	4H	22,7	24,0	23,2	24,2	24,5	22,8	24,0	23,2	24,3	24,6
	6H	23,3	24,3	23,6	24,6	25,0	23,3	24,4	23,6	24,7	25,1
	8H	23,4	24,4	23,7	24,7	25,2	23,5	24,5	23,8	24,8	25,2
	12H	23,5	24,5	23,8	24,8	25,3	23,5	24,5	23,9	24,9	25,3
4H	2H	21,3	22,5	21,7	22,8	23,0	21,3	22,5	21,7	22,8	23,1
	3H	23,0	24,0	23,4	24,4	24,8	23,1	24,1	23,4	24,4	24,9
	4H	23,7	24,6	24,2	25,1	25,6	23,7	24,7	24,2	25,1	25,6
	6H	24,3	25,2	24,8	25,5	25,9	24,3	25,2	24,8	25,6	26,0
	8H	24,5	25,3	25,0	25,7	26,0	24,5	25,3	25,0	25,7	26,1
	12H	24,6	25,3	25,1	25,7	26,2	24,6	25,3	25,1	25,7	26,2
8H	4H	24,0	24,8	24,5	25,2	25,6	24,0	24,8	24,5	25,2	25,6
	6H	24,7	25,3	25,2	25,8	26,4	24,8	25,4	25,3	25,9	26,4
	8H	25,0	25,6	25,5	26,1	26,7	25,1	25,6	25,6	26,1	26,8
	12H	25,2	25,7	25,8	26,2	26,8	25,3	25,7	25,8	26,2	26,8
12H	4H	24,0	24,7	24,5	25,1	25,6	24,0	24,7	24,5	25,2	25,6
	6H	24,8	25,4	25,3	25,9	26,5	24,9	25,4	25,4	25,9	26,6
	8H	25,1	25,6	25,7	26,1	26,7	25,2	25,6	25,7	26,1	26,7
Variations with the observer position for the luminaire spacings, S:											
S = 1.0H				0,1 / -0,1				0,1 / -0,1			
S = 1.5H				0,1 / -0,2				0,1 / -0,2			
S = 2.0H				0,4 / -0,5				0,4 / -0,5			

Coefficients of Utilization

Ceiling reflectance	80			70			50			30			10			0		
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR		(RCR: Room Cavity Ratio)			Room Values are expressed as percentage of Lumen delivered to the task surface													
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	108	104	99	95	106	101	97	94	97	94	91	93	90	88	89	87	85	83
2	99	90	83	77	96	88	82	76	85	79	75	81	77	73	78	74	71	69
3	90	79	71	64	87	77	70	64	74	68	62	72	66	61	69	64	60	58
4	82	70	61	54	80	69	60	54	66	59	53	64	57	52	61	56	52	49
5	75	62	53	47	73	61	53	46	59	52	46	57	51	45	55	49	45	43
6	70	56	47	41	68	55	47	41	53	46	40	52	45	40	50	44	39	37
7	65	51	42	36	63	50	42	36	49	41	36	47	40	35	46	40	35	33
8	60	47	38	32	59	46	38	32	44	37	32	43	36	31	42	36	31	29
9	56	43	34	29	55	42	34	29	41	34	29	40	33	28	39	33	28	26
10	53	39	31	26	51	39	31	26	38	31	26	37	30	26	36	30	26	24

Light Measurement Report


Print date: 10-2-2025
Measurement date and time: 10-2-2025 15:46:19 – Measurement no. VFR-250210-3331-MS
Measurement tracking No. and Link: [VT250210-007947](#)
Operator:



Luminaire budgetary diagram

Uncorrected, comprehensive UGR table according to 117-1995

LAMPS (number of lamps)



Conditions

H = Room height	Flux = 1745 lm	p(%)		
H _{down} = Lamp distance from ceiling =	0.00 m	Line type	Ceiling reflectance	Wall reflectance
H _{work} = Work area height from floor =	0.00 m	-----	70	50
E _{work} = Average lux on work area =	100 lx	-----	50	30
				Floor reflectance
				20

Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
57,8 lm	165 lm	249 lm	300 lm	310 lm	279 lm	214 lm	127 lm	38,0 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
1,05 lm	0,575 lm	0,639 lm	0,775 lm	0,733 lm	0,678 lm	0,551 lm	0,367 lm	0,127 lm

Light Measurement Report

Print date: 10-2-2025

Measurement date and time: 10-2-2025 15:46:19 – Measurement no. VFR-250210-3331-MS

Measurement tracking No. and Link: [VT250210-007947](#)

Operator:



Outdoor Light Planning

Lumen per Zone

Zone (γ)	Lumen	% Total
0-10°	58 lm	3,3%
10-20°	165 lm	9,5%
20-30°	249 lm	14,3%
30-40°	300 lm	17,2%
40-50°	310 lm	17,7%
50-60°	279 lm	16,0%
60-70°	214 lm	12,3%
70-80°	127 lm	7,3%
80-90°	38 lm	2,2%
90-100°	1 lm	0,1%
100-110°	1 lm	0,0%
110-120°	1 lm	0,0%
120-130°	1 lm	0,0%
130-140°	1 lm	0,0%
140-150°	1 lm	0,0%
150-160°	1 lm	0,0%
160-170°	0 lm	0,0%
170-180°	0 lm	0,0%
Total	1745 lm	100,0%

Intensity peaks

Max intensity	611 cd
Intensity, 90°	6 cd
Intensity, 0°	611 cd

Zonal Lumen summary

Zone (γ)	Lumen	% Total
0-30°	472 lm	27,1%
0-40°	772 lm	44,2%
0-60°	1361 lm	78,0%
60-90°	379 lm	21,7%
70-100°	166 lm	9,5%
90-120°	2 lm	0,1%
0-90°	1740 lm	99,7%
90-180°	5 lm	0,3%
0-180°	1745 lm	100,0%


BUG rating

	Lumen	% Total
Forward light		
Low(0-30°)	236 lm	13,5%
Medium(30-60°)	444 lm	25,4%
High(60-80°)	171 lm	9,8%
Very high(80-90°)	19 lm	1,1%
Back light		
Low(0-30°)	236 lm	13,5%
Medium(30-60°)	444 lm	25,4%
High(60-80°)	171 lm	9,8%
Very high(80-90°)	19 lm	1,1%
Uplight		
Low(90-100°)	1 lm	0,1%
High(100-180°)	4 lm	0,3%

IESNA TM-15-07

Luminaire Classification System For Outdoor Luminaires

BUG rating B1 U1 G1



Light Measurement Report

Print date: 10-2-2025
Measurement date and time: 10-2-2025 15:46:19 – Measurement no. VFR-250210-3331-MS
Measurement tracking No. and Link: [VT250210-007947](#)
Operator:




Power Details


Input Power

Power feed to light source	18,0 W
Frequency of input power	50 Hz
RMS Input voltage feed, V_{RMS}	230 V
RMS Input current feed, I_{RMS}	0,084 A
Volt-Ampere or apparent power = $V_{RMS} \cdot I_{RMS}$	19,31 VA
Displacement factor of AC power feed	0,96
Power factor of AC current feed	0,93
Total harmonic distortion of the current	26,56%
Total harmonic distortion of the voltage	0,07%

Input Power Curve



Efficiency



Stabilization Details

Warmup Conditions

Stable period	15 min
Stable change max	2,0%
Minimum time	15 min

Color Temperature Change

CCT start	4996 K
CCT shift	+4 K
CCT end	5000 K


Warmup Result

Total warmup time	Lamp stabilized in 15 min 1 sec
Warmup variation	+0,1%

Output Change

Output start	1745 lm
Output change	+ 1m
Output end	1745 lm

Stabilization Curve



Light Measurement Report

Print date: 10-2-2025
Measurement date and time: 10-2-2025 15:46:19 – Measurement no. VFR-250210-3331-MS
Measurement tracking No. and Link: [VT250210-007947](#)
Operator:



Flicker /TLA details

Flicker Meter Type Viso Systems LabFlicker
Frequency of input power 50 Hz
Flicker/TLA sample rate 20000 samples/s

Measurement time
PstLM 180 sec
All other indices 1,2 sec

Flicker indices according to Illuminating Engineering Society (IES)
Flicker frequency 100 Hz
Percent Flicker 29,08 %
Flicker index 0,09



Flicker indices according to California Energy Commission (CEC) 2016b
JA8/10 40 Hz 0,18 %
JA8/10 90 Hz 0,29 %
JA8/10 200 Hz 28,4 %
JA8/10 400 Hz 29,06 %
JA8/10 1000 Hz 29,13 %

TLA indices (re IEC TR 61547-1, IEC 61000-3-3 and IEC 61000-4-15)
PstLM value (F < 80 Hz) 0,16
SVM value (80 < F < 2000 Hz) 1,1

Flicker indices according to Lighting Research Center (2015)
Perception metric, Assist Mp 0,11

Flicker frame (frame of one flicker period in time domain)

Flicker FFT (flicker curve in frequency domain)



IEEE 1789 Frequency/modulation plot

