

Light Measurement Report

Print date: 25-11-2024

Measurement date and time: 25-11-2024 16:36:45 – Measurement no. VFR-241125-2135-MS

Measurement tracking No. and Link: [VT241125-007867](https://www.viso-systems.com/VT241125-007867)

Operator:



Laboratory and Equipment

Laboratory Owner and Location
Goniospectrometer System and Type
Sensor Name, Calibr. Date and Serial No.
Spectrometer Manufacturer and Model

Viso Systems, Copenhagen V, Denmark
LabSpion – Type C, horizontal
LabSensor Model2 – 11-1-2024 – 3130191315
Ibsen Photonics, Denmark – Freedom VIS (Custom Viso)

Measurement Conditions

Number of C-planes and Resolution
 γ (gamma)-Resolution
Test Distance
Input Power, Power and Displ. Factors
Input RMS Voltage and Current
Frequency of Input Power
Warm-up Time and Variation

72 planes – 5°
5°
1,99 m
20,5 W – PF 0,79 – DPF 0,99
230 V – 0,113 A
50 Hz
Lamp stabilized in 15 min 2 sec – 2,0%

Tested Light Source



Product Name
Item No. and Manufacturer
Product Description (line 1)
SWITCH

807894-2700K-20W
807894-2700K-20W – Dutchfulfillment
3-FASE RAILSPOT | ROSALIN | 10W-20W-30W | ZWART | DIMBAAR | CCT-

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)
Efficiency
Peak Intensity and Beam Angle
Correlated Color Temperature, Target/Measured
Color Rendering Index
Color Rendering TM30-18
Color Shift, CIE duv and MacAdam Steps
Flicker

1473 lm – 0,08% / 99,92%
72 lm/W
4255 cd – 29,1°
CCT = 2700 K / 2794 K
CRI 92,9
 R_f 91,7 – R_g 96,4
Duv 0,0026 – SDCM 4,5
SVM 0,04 – PstLM 0,03



Light Measurement Report

Print date: 25-11-2024

Measurement date and time: 25-11-2024 16:36:45 – Measurement no. VFR-241125-2135-MS


Measurement tracking No. and Link: [VT241125-007867](https://vt241125-007867)

Operator:



Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	1473 lm
Lumen Up% / Down%	0,08% / 99,92%
Peak Intensity	4255 cd
Beam Angle (50%)	29,1°
Beam Angle (90%)	29,5°
Beam Angle (10%)	28,6°

Cut-off Angle

Average 2,5%	77,7°
--------------	-------

Field Angle

Average 10%	65,8°
-------------	-------


Intensity Ratio

In 120° cone	99,7%
In 90° cone	98,7%

C000-C180

C090-C270

Linear distribution diagram - Intensity (candela) vs γ -angle



Light Measurement Report

Print date: 25-11-2024


Measurement date and time: 25-11-2024 16:36:45 – Measurement no. VFR-241125-2135-MS

Measurement tracking No. and Link: [VT241125-007867](https://www.viso-systems.com/VT241125-007867)

Operator:




Iso-intensity Diagram (Iso-candela)



90 %	3772,2 cd
80 %	3353,0 cd
70 %	2933,9 cd
60 %	2514,8 cd
50 %	2095,6 cd
40 %	1676,5 cd
30 %	1257,4 cd
20 %	838,3 cd
10 %	419,1 cd

Peak intensity: 4191,3 cd
Number of c-planes: 72

Iso-illuminance Diagram (Iso-lux)



50,0 %	232,7 lx
30,0 %	139,6 lx
10,0 %	46,5 lx
5,0 %	23,3 lx
3,0 %	14,0 lx

Peak illuminance: 465,5 lx
Mounting height: 3,0 m
Number of c-planes: 72

Light Measurement Report

Print date: 25-11-2024

Measurement date and time: 25-11-2024 16:36:45 – Measurement no. VFR-241125-2135-MS

Measurement tracking No. and Link: [VT241125-007867](https://www.viso-systems.com/VT241125-007867)

Operator:




Color details


Correlated Color Temperature, Target CCT = 2700 K
 Correlated Color Temperature, Measured CCT = 2794 K
 Color Rendering Index CRI 92,9
 Color Rendering Index, R9 (red component) R9 = 52,4
 Color Rendering TM30-18 R_f 91,7 – R_g 96,4
 Color Quality Scale CQS = 90,8

MacAdam Steps SDCM = 4,5
 Color coordinates CIE 1931 (x;y) = (0,460;0,411)
 Color coordinate CIEs 1960 (u;v) = (0,263;0,352)
 Color deviation from BBL Duv = 0,0026
 Color coordinate CIEs 1976 (CIELUV) (u';v') = (0,263;0,527)


CIE 1931



CIE 1931 – zoomed on Planckian locus




Color Rendering Index per reference color (CIE 1995)




CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
92,9	96,7	99,5	93,9	93,0	97,6	91,0	78,8	52,4	92,2	96,5	84,0	94,1	99,3	86,3

Spectral power distribution (SPD) / W/nm – 0-100%




TM30-18 R_f-values per hue bin



TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
89,3	92,5	93,5	93,7	95,0	95,7	92,4	95,2	92,8	90,7	91,5	90,7	90,1	87,0	90,7	84,9

Color Quality Scale by reference color



CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
86,2	94,2	93,2	92,2	93,2	93,6	93,7	94,0	93,0	91,2	92,3	93,3	93,0	84,7	85,6

Light Measurement Report

Print date: 25-11-2024


Measurement date and time: 25-11-2024 16:36:45 – Measurement no. VFR-241125-2135-MS

Measurement tracking No. and Link: [VT241125-007867](https://www.viso-systems.com/VT241125-007867)

Operator:



Beam Details



Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3,3	6,6	9,8	13,1	16,4	19,7	23	26,2	29,5	32,8	36,1	39,4	42,7	45,9	49,2	52,5	55,8	59,1	62,3	65,6	ft
4186	1047	465	262	167	116	85	65	52	42	35	29	25	21	19	16	14	13	12	10	lux
388,9	97,2	43,2	24,3	15,6	10,8	7,9	6,1	4,8	3,9	3,2	2,7	2,3	2	1,7	1,5	1,3	1,2	1,1	1	fc

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
4186	4108	3872	3637	3308	2940	2572	2209	1846	1547	1277	1034	902	769	664	570	471	350	229	149	cd
100%	98%	93%	87%	79%	70%	61%	53%	44%	37%	30%	25%	22%	18%	16%	14%	11%	8%	5%	4%	of 0°val

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
4186	4065	3855	3646	3310	2939	2569	2201	1833	1538	1263	1028	897	765	666	576	475	351	226	149	cd
100%	97%	92%	87%	79%	70%	61%	53%	44%	37%	30%	25%	21%	18%	16%	14%	11%	8%	5%	4%	of 0°val

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
4186	4108	3872	3637	3308	2940	2572	2209	1846	1547	1277	1034	902	769	664	570	471	350	229	149	cd
100%	98%	93%	87%	79%	70%	61%	53%	44%	37%	30%	25%	22%	18%	16%	14%	11%	8%	5%	4%	of 0°val

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
4186	4065	3855	3646	3310	2939	2569	2201	1833	1538	1263	1028	897	765	666	576	475	351	226	149	cd
100%	97%	92%	87%	79%	70%	61%	53%	44%	37%	30%	25%	21%	18%	16%	14%	11%	8%	5%	4%	of 0°val

Light Measurement Report

Print date: 25-11-2024

Measurement date and time: 25-11-2024 16:36:45 – Measurement no. VFR-241125-2135-MS

Measurement tracking No. and Link: [VT241125-007867](#)

Operator:



Light Planning – UGR table

Uncorrected, comprehensive UGR table according to 117-1995

Reflectances		70	70	50	50	30	70	70	50	50	30
	ρ Ceiling	70	70	50	50	30	70	70	50	50	30
	ρ Walls	50	30	50	30	30	50	30	50	30	30
	ρ Floor	20	20	20	20	20	20	20	20	20	20
Room size		Viewed Crosswise					Viewed Endwise				
H = mounting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	Y										
2H	2H	16,0	16,5	16,1	16,7	16,9	16,0	16,6	16,1	16,8	17,0
	3H	15,7	16,4	16,1	16,6	16,7	15,7	16,4	16,1	16,6	16,8
	4H	15,6	16,3	16,0	16,5	16,7	15,7	16,3	16,1	16,5	16,8
	6H	15,6	16,1	15,9	16,4	16,8	15,7	16,2	16,0	16,5	16,8
	8H	15,6	16,1	15,9	16,4	16,8	15,6	16,1	15,9	16,4	16,8
	12H	15,5	16,0	15,9	16,4	16,8	15,6	16,0	15,9	16,4	16,8
4H	2H	15,6	16,3	16,0	16,5	16,7	15,7	16,3	16,1	16,5	16,8
	3H	15,5	16,0	15,9	16,4	16,8	15,6	16,0	15,9	16,4	16,8
	4H	15,4	15,8	15,8	16,3	16,8	15,4	15,9	15,8	16,3	16,8
	6H	15,3	15,8	15,8	16,1	16,5	15,3	15,8	15,8	16,2	16,5
	8H	15,2	15,7	15,7	16,0	16,4	15,3	15,7	15,8	16,1	16,4
	12H	15,2	15,5	15,7	15,9	16,4	15,2	15,6	15,7	16,0	16,4
8H	4H	15,2	15,7	15,7	16,0	16,4	15,3	15,7	15,8	16,1	16,4
	6H	15,2	15,5	15,7	15,9	16,4	15,2	15,5	15,7	16,0	16,5
	8H	15,2	15,4	15,7	15,9	16,5	15,2	15,4	15,7	15,9	16,6
	12H	15,1	15,3	15,7	15,8	16,4	15,1	15,3	15,7	15,8	16,4
12H	4H	15,2	15,5	15,7	15,9	16,4	15,2	15,6	15,7	16,0	16,4
	6H	15,2	15,4	15,7	15,9	16,5	15,2	15,4	15,7	15,9	16,6
	8H	15,1	15,3	15,7	15,8	16,4	15,1	15,3	15,7	15,8	16,4

Variations with the observer position for the luminaire spacings, S:

S = 1.0H	6,2 / -14,0	6,0 / -14,2
S = 1.5H	8,9 / -18,5	8,8 / -18,5
S = 2.0H	10,9 / -21,2	10,7 / -21,4

Coefficients of Utilization

Ceiling reflectance	80			70			50			30			10			0		
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)																	
	Room Values are expressed as percentage of Lumen delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	112	110	108	112	110	108	106	106	104	103	102	101	100	99	98	97	95
2	110	106	102	99	108	104	101	98	101	98	96	98	96	94	95	94	92	91
3	105	100	96	93	104	99	95	92	96	93	90	94	91	89	92	89	88	86
4	101	95	90	87	100	94	90	86	92	88	85	90	87	84	88	86	83	82
5	97	90	86	82	96	90	85	82	88	84	81	86	83	80	85	82	80	78
6	94	86	81	78	92	86	81	77	84	80	77	83	79	76	82	78	76	75
7	90	82	78	74	89	82	77	74	81	76	73	80	76	73	79	75	73	72
8	87	79	74	71	86	78	74	71	77	73	70	77	73	70	76	72	70	69
9	84	76	71	68	83	75	71	68	74	70	67	74	70	67	73	69	67	66
10	81	73	68	65	80	72	68	65	72	68	65	71	67	64	70	67	64	63

Light Measurement Report

Print date: 25-11-2024

Measurement date and time: 25-11-2024 16:36:45 – Measurement no. VFR-241125-2135-MS

Measurement tracking No. and Link: [VT241125-007867](https://www.viso-systems.com/VT241125-007867)


Operator:



Luminaire budgetary diagram

Uncorrected, comprehensive UGR table according to 117-1995

LAMPS (number of lamps)



Conditions

H = Room height	Flux = 1473 lm	$\rho(\%)$			
H _{down} = Lamp distance from ceiling =	0.00 m	Line type	Ceiling reflectance	Wall reflectance	Floor reflectance
H _{work} = Work area height from floor =	0.00 m	-----	70	50	30
E _{work} = Average lux on work area =	100 lx	_____	50	30	20

Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
337 lm	550 lm	377 lm	178 lm	19,6 lm	7,42 lm	2,04 lm	0,470 lm	0,143 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0,144 lm	0,139 lm	0,129 lm	0,117 lm	0,117 lm	0,140 lm	0,194 lm	0,195 lm	0,065 lm

Light Measurement Report

Print date: 25-11-2024

Measurement date and time: 25-11-2024 16:36:45 – Measurement no. VFR-241125-2135-MS

Measurement tracking No. and Link: [VT241125-007867](#)

Operator:



Outdoor Light Planning

Lumen per Zone

Zone (γ)	Lumen	% Total
0-10°	337 lm	22,8%
10-20°	550 lm	37,3%
20-30°	377 lm	25,6%
30-40°	178 lm	12,1%
40-50°	20 lm	1,3%
50-60°	7 lm	0,5%
60-70°	2 lm	0,1%
70-80°	0 lm	0,0%
80-90°	0 lm	0,0%
90-100°	0 lm	0,0%
100-110°	0 lm	0,0%
110-120°	0 lm	0,0%
120-130°	0 lm	0,0%
130-140°	0 lm	0,0%
140-150°	0 lm	0,0%
150-160°	0 lm	0,0%
160-170°	0 lm	0,0%
170-180°	0 lm	0,0%
Total	1473 lm	100,0%

Intensity peaks

Max intensity	4255 cd
Intensity, 90°	0 cd
Intensity, 0°	4186 cd

Zonal Lumen summary


Zone (γ)	Lumen	% Total
0-30°	1264 lm	85,8%
0-40°	1442 lm	97,9%
0-60°	1469 lm	99,7%
60-90°	3 lm	0,2%
70-100°	1 lm	0,1%
90-120°	0 lm	0,0%
0-90°	1472 lm	99,9%
90-180°	1 lm	0,1%
0-180°	1473 lm	100,0%

BUG rating

	Lumen	% Total
Forward light		
Low(0-30°)	628 lm	42,6%
Medium(30-60°)	104 lm	7,1%
High(60-80°)	1 lm	0,1%
Very high(80-90°)	0 lm	0,0%
Back light		
Low(0-30°)	628 lm	42,6%
Medium(30-60°)	104 lm	7,1%
High(60-80°)	1 lm	0,1%
Very high(80-90°)	0 lm	0,0%
Uplight		
Low(90-100°)	0 lm	0,0%
High(100-180°)	1 lm	0,1%

IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B2 U1 G0



Light Measurement Report

Print date: 25-11-2024

Measurement date and time: 25-11-2024 16:36:45 – Measurement no. VFR-241125-2135-MS

Measurement tracking No. and Link: [VT241125-007867](#)

Operator:




Power Details


Input Power

Power feed to light source	20,5 W
Frequency of input power	50 Hz
RMS Input voltage feed, V_{RMS}	230 V
RMS Input current feed, I_{RMS}	0,113 A
Volt-Ampere or apparent power = $V_{RMS} * I_{RMS}$	26,08 VA
Displacement factor of AC power feed	0,99
Power factor of AC current feed	0,79
Total harmonic distortion of the current	75,12%
Total harmonic distortion of the voltage	0,08%

Input Power Curve



Efficiency



Stabilization Details

Warmup Conditions

Stable period	15 min
Stable change max	2,0%
Minimum time	15 min

Color Temperature Change

CCT start	2702 K
CCT shift	-2 K
CCT end	2700 K


Warmup Result

Total warmup time	Lamp stabilized in 15 min 2 sec
Warmup variation	-1,1%

Output Change

Output start	1489 lm
Output change	-16 lm
Output end	1473 lm

Stabilization Curve



Light Measurement Report

Print date: 25-11-2024

Measurement date and time: 25-11-2024 16:36:45 – Measurement no. VFR-241125-2135-MS

Measurement tracking No. and Link: [VT241125-007867](#)

Operator:



Flicker /TLA details

Flicker Meter Type: Viso Systems LabFlicker
 Frequency of input power: 50 Hz
 Flicker/TLA sample rate: 20000 samples/s

Measurement time
 PstLM: 180 sec
 All other indices: 1,2 sec

Flicker indices according to Illuminating Engineering Society (IES)

Flicker frequency: 100 Hz
 Percent Flicker: 1,35 %
 Flicker index: 0

Flicker indices according to California Energy Commission (CEC) 2016b

JA8/10 40 Hz: 0,04 %
 JA8/10 90 Hz: 0,04 %
 JA8/10 200 Hz: 1,16 %
 JA8/10 400 Hz: 1,28 %
 JA8/10 1000 Hz: 1,33 %


TLA indices (re IEC TR 61547-1, IEC 61000-3-3 and IEC 61000-4-15)

PstLM value (F < 80 Hz): 0,03
 SVM value (80 < F < 2000 Hz): 0,04


Flicker indices according to Lighting Research Center (2015)

Perception metric, Assist Mp: 0,02

Flicker frame (frame of one flicker period in time domain)



Flicker FFT (flicker curve in frequency domain)



IEEE 1789 Frequency/modulation plot

