

Light Measurement Report

Print date: 21-5-2025

Measurement date and time: 21-5-2025 09:05:08 – Measurement no. VFR-250521-1342-MS

Measurement tracking No. and Link: [VT250521-002630](#)

Operator:



Laboratory and Equipment

Laboratory Owner and Location
Goniospectrometer System and Type
Sensor Name, Calibr. Date and Serial No.
Spectrometer Manufacturer and Model

Viso Systems, Copenhagen V, Denmark
LabSpion – Type C, horizontal
LabSensor Model2 – 11-1-2024 – 3130191315
Ibsen Photonics, Denmark – Freedom VIS (Custom Viso)

Measurement Conditions

Number of C-planes and Resolution
 γ (gamma)-Resolution
Test Distance
Input Power, Power and Displ. Factors
Input RMS Voltage and Current
Frequency of Input Power
Warm-up Time and Variation

16 planes – 22,5°
5°
6,49 m
35,1 W – PF 0,97 – DPF 0,97
230 V – 0,158 A
50 Hz
Lamp stabilized in 17 min 30 sec – 2,0%

Tested Light Source




Product Name
Item No. and Manufacturer
Product Description (line 1)

811549-6500K-36W
811549-6500K-36W – Dutchfulfillment
LED LOUVRE PANEEL | KASTRA | 60X60CM | 36W | CCT-SWITCH | WIT

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)
Efficiency
Peak Intensity and Beam Angle
Correlated Color Temperature, Target/Measured
Color Rendering Index
Color Rendering TM30-18
Color Shift, CIE duv and MacAdam Steps
Flicker

3735 lm – 0,51% / 99,49%
106 lm/W
2195 cd – 80,5°
CCT = 6500 K / 6273 K
CRI 83,7
 R_f 83,6 – R_g 92,2
Duv 0,0081 – SDCM 11,1
SVM 0 – PstLM 0,01



Light Measurement Report

Print date: 21-5-2025

Measurement date and time: 21-5-2025 09:05:08 – Measurement no. VFR-250521-1342-MS


Measurement tracking No. and Link: [VT250521-002630](#)

Operator:



Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	3735 lm
Lumen Up% / Down%	0,51% / 99,49%
Peak Intensity	2195 cd
Beam Angle (50%)	80,5°
Beam Angle (90%)	80,5°
Beam Angle (10%)	80,5°

Cut-off Angle

Average 2,5%	157,4°
--------------	--------

Field Angle

Average 10%	120,9°
-------------	--------


Intensity Ratio

In 120° cone	92,3%
In 90° cone	76,8%

C000-C180

C090-C270

Linear distribution diagram - Intensity (candela) vs γ -angle



Light Measurement Report

Print date: 21-5-2025


Measurement date and time: 21-5-2025 09:05:08 – Measurement no. VFR-250521-1342-MS

Measurement tracking No. and Link: [VT250521-002630](#)

Operator:



Iso-intensity Diagram (Iso-candela)




90 %	1975,6 cd
80 %	1756,1 cd
70 %	1536,6 cd
60 %	1317,1 cd
50 %	1097,6 cd
40 %	878,0 cd
30 %	658,5 cd
20 %	439,0 cd
10 %	219,5 cd

Peak intensity: 2195,1 cd

Number of c-planes: 16

Iso-illuminance Diagram (Iso-lux)



50,0 %	122,0 lx
30,0 %	73,2 lx
10,0 %	24,4 lx
5,0 %	12,2 lx
3,0 %	7,3 lx

Peak illuminance: 243,9 lx

Mounting height: 3,0 m

Number of c-planes: 16

Light Measurement Report

Print date: 21-5-2025

Measurement date and time: 21-5-2025 09:05:08 – Measurement no. VFR-250521-1342-MS

Measurement tracking No. and Link: [VT250521-002630](https://www.viso-systems.com/VT250521-002630)

Operator:




Color details


Correlated Color Temperature, Target CCT = 6500 K
 Correlated Color Temperature, Measured CCT = 6273 K
 Color Rendering Index CRI 83,7
 Color Rendering Index, R9 (red component) R9 = 5,2
 Color Rendering TM30-18 R_f 83,6 – R_g 92,2
 Color Quality Scale CQS = 82,2

MacAdam Steps
 Color coordinates CIE 1931 (x;y) = (0,314;0,324)
 Color coordinate CIEs 1960 (u;v) = (0,200;0,310)
 Color deviation from BBL Duv = 0,0081
 Color coordinate CIEs 1976 (CIELUV) (u';v') = (0,200;0,466)


CIE 1931



CIE 1931 – zoomed on Planckian locus




Color Rendering Index per reference color (CIE 1995)




CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
81,2	90,2	94,7	80,6	81,2	85,6	87,7	67,9	5,2	76,4	80,3	57,4	84,2	97,5	74,3

Spectral power distribution (SPD) / W/nm – 0-100%




TM30-18 R_f-values per hue bin



TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
75,1	85,6	84,1	90,2	87,7	92,1	91,0	83,5	82,6	73,7	79,7	92,6	86,0	81,7	69,9	84,4

Color Quality Scale by reference color



CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
79,9	97,2	82,3	75,1	78,7	80,2	84,1	89,2	97,0	91,4	87,4	85,8	84,4	70,6	74,8

Light Measurement Report

Print date: 21-5-2025


Measurement date and time: 21-5-2025 09:05:08 – Measurement no. VFR-250521-1342-MS

Measurement tracking No. and Link: [VT250521-002630](https://www.viso-systems.com/VT250521-002630)

Operator:



Beam Details



Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3,3	6,6	9,8	13,1	16,4	19,7	23	26,2	29,5	32,8	36,1	39,4	42,7	45,9	49,2	52,5	55,8	59,1	62,3	65,6	ft
2195	549	244	137	88	61	45	34	27	22	18	15	13	11	10	9	8	7	6	5	lux
203,9	51	22,7	12,7	8,2	5,7	4,2	3,2	2,5	2	1,7	1,4	1,2	1	0,9	0,8	0,7	0,6	0,6	0,5	fc

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
2195	2192	2136	2060	1968	1851	1686	1443	1116	780	521	341	226	158	114	78	47	21	5	1	cd
100%	100%	97%	94%	90%	84%	77%	66%	51%	36%	24%	16%	10%	7%	5%	4%	2%	1%	0%	0%	of 0°val

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
2195	2192	2136	2060	1968	1851	1686	1443	1116	780	521	341	226	158	114	78	47	21	5	1	cd
100%	100%	97%	94%	90%	84%	77%	66%	51%	36%	24%	16%	10%	7%	5%	4%	2%	1%	0%	0%	of 0°val

Intensities in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
2195	2192	2136	2060	1968	1851	1686	1443	1116	780	521	341	226	158	114	78	47	21	5	1	cd
100%	100%	97%	94%	90%	84%	77%	66%	51%	36%	24%	16%	10%	7%	5%	4%	2%	1%	0%	0%	of 0°val

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
2195	2192	2136	2060	1968	1851	1686	1443	1116	780	521	341	226	158	114	78	47	21	5	1	cd
100%	100%	97%	94%	90%	84%	77%	66%	51%	36%	24%	16%	10%	7%	5%	4%	2%	1%	0%	0%	of 0°val

Light Measurement Report

Print date: 21-5-2025

Measurement date and time: 21-5-2025 09:05:08 – Measurement no. VFR-250521-1342-MS

Measurement tracking No. and Link: [VT250521-002630](#)

Operator:



Light Planning – UGR table

Uncorrected, comprehensive UGR table according to 117-1995

Reflectances		70	70	50	50	30	70	70	50	50	30
	ρ Ceiling	70	70	50	50	30	70	70	50	50	30
	ρ Walls	50	30	50	30	30	50	30	50	30	30
	ρ Floor	20	20	20	20	20	20	20	20	20	20
Room size		Viewed Crosswise					Viewed Endwise				
H = mounting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	Y										
2H	2H	15,4	16,4	15,6	16,6	16,8	15,4	16,4	15,6	16,6	16,8
	3H	15,7	16,7	16,1	17,0	17,2	15,7	16,7	16,1	17,0	17,2
	4H	15,9	16,8	16,3	17,1	17,4	15,9	16,8	16,3	17,1	17,4
	6H	16,1	16,9	16,4	17,2	17,6	16,1	16,9	16,4	17,2	17,6
	8H	16,1	16,9	16,5	17,2	17,7	16,1	16,9	16,5	17,2	17,7
	12H	16,1	16,9	16,5	17,3	17,7	16,1	16,9	16,5	17,3	17,7
4H	2H	15,4	16,4	15,8	16,7	16,9	15,4	16,4	15,8	16,7	16,9
	3H	16,0	16,8	16,4	17,2	17,6	16,0	16,8	16,4	17,2	17,6
	4H	16,2	17,0	16,7	17,4	17,9	16,2	17,0	16,7	17,4	17,9
	6H	16,5	17,2	17,0	17,5	17,9	16,5	17,2	17,0	17,5	17,9
	8H	16,6	17,2	17,1	17,6	17,9	16,6	17,2	17,1	17,6	17,9
	12H	16,6	17,1	17,1	17,5	18,0	16,6	17,1	17,1	17,5	18,0
8H	4H	16,3	17,0	16,8	17,3	17,7	16,3	17,0	16,8	17,3	17,7
	6H	16,7	17,1	17,2	17,6	18,1	16,7	17,1	17,2	17,6	18,1
	8H	16,8	17,2	17,3	17,7	18,4	16,8	17,2	17,3	17,7	18,4
	12H	16,9	17,2	17,5	17,8	18,4	16,9	17,2	17,5	17,8	18,4
12H	4H	16,3	16,8	16,8	17,2	17,7	16,3	16,8	16,8	17,2	17,7
	6H	16,7	17,1	17,2	17,6	18,3	16,7	17,1	17,2	17,6	18,3
	8H	16,8	17,2	17,4	17,7	18,3	16,8	17,2	17,4	17,7	18,3

Variations with the observer position for the luminaire spacings, S:

S = 1.0H	0,5 / -0,9	0,5 / -0,9
S = 1.5H	1,6 / -1,6	1,6 / -1,6
S = 2.0H	2,8 / -2,1	2,8 / -2,1

Coefficients of Utilization

Ceiling reflectance	80			70			50			30			10			0		
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)																	
	Room Values are expressed as percentage of Lumen delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	99
1	111	108	104	101	109	105	102	100	101	99	96	97	95	93	94	92	91	89
2	104	97	92	87	101	95	90	86	92	88	84	89	85	82	86	83	80	79
3	96	88	81	76	94	86	80	76	84	78	74	81	77	73	78	75	72	70
4	90	80	73	67	88	79	72	67	76	71	66	74	69	65	72	68	64	62
5	84	73	66	60	82	72	65	60	70	64	59	68	63	58	66	62	58	56
6	78	67	59	54	76	66	59	54	64	58	53	63	57	53	61	56	52	51
7	73	62	54	49	72	61	54	49	59	53	48	58	52	48	57	52	48	46
8	69	57	50	44	67	56	49	44	55	49	44	54	48	44	53	47	44	42
9	65	53	46	41	63	52	45	41	51	45	40	50	44	40	49	44	40	38
10	61	49	42	37	60	49	42	37	48	41	37	47	41	37	46	41	37	35

Light Measurement Report

Print date: 21-5-2025

Measurement date and time: 21-5-2025 09:05:08 – Measurement no. VFR-250521-1342-MS

Measurement tracking No. and Link: [VT250521-002630](#)


Operator:



Luminaire budgetary diagram

Uncorrected, comprehensive UGR table according to 117-1995

LAMPS (number of lamps)



Conditions

H = Room height	Flux = 3735 lm				
H _{down} = Lamp distance from ceiling =	0.00 m	Line type	Ceiling reflectance	ρ(%) Wall reflectance	Floor reflectance
H _{work} = Work area height from floor =	0.00 m	-----	70	50	30
E _{work} = Average lux on work area =	100 lx	—————	50	30	20

Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
207 lm	580 lm	848 lm	886 lm	609 lm	316 lm	161 lm	83,3 lm	25,3 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
2,30 lm	1,79 lm	2,37 lm	2,80 lm	2,86 lm	2,69 lm	2,20 lm	1,49 lm	0,529 lm

Light Measurement Report

Print date: 21-5-2025

Measurement date and time: 21-5-2025 09:05:08 – Measurement no. VFR-250521-1342-MS

Measurement tracking No. and Link: [VT250521-002630](#)

Operator:



Outdoor Light Planning

Lumen per Zone

Zone (γ)	Lumen	% Total
0-10°	207 lm	5,5%
10-20°	580 lm	15,5%
20-30°	848 lm	22,7%
30-40°	886 lm	23,7%
40-50°	609 lm	16,3%
50-60°	316 lm	8,4%
60-70°	161 lm	4,3%
70-80°	83 lm	2,2%
80-90°	25 lm	0,7%
90-100°	2 lm	0,1%
100-110°	2 lm	0,0%
110-120°	2 lm	0,1%
120-130°	3 lm	0,1%
130-140°	3 lm	0,1%
140-150°	3 lm	0,1%
150-160°	2 lm	0,1%
160-170°	1 lm	0,0%
170-180°	1 lm	0,0%
Total	3735 lm	100,0%

Intensity peaks

Max intensity	2195 cd
Intensity, 90°	5 cd
Intensity, 0°	2195 cd

Zonal Lumen summary


Zone (γ)	Lumen	% Total
0-30°	1635 lm	43,8%
0-40°	2521 lm	67,5%
0-60°	3446 lm	92,3%
60-90°	270 lm	7,2%
70-100°	111 lm	3,0%
90-120°	6 lm	0,2%
0-90°	3716 lm	99,5%
90-180°	19 lm	0,5%
0-180°	3735 lm	100,0%

BUG rating

	Lumen	% Total
Forward light		
Low(0-30°)	817 lm	21,9%
Medium(30-60°)	906 lm	24,3%
High(60-80°)	122 lm	3,3%
Very high(80-90°)	13 lm	0,3%
Back light		
Low(0-30°)	817 lm	21,9%
Medium(30-60°)	906 lm	24,3%
High(60-80°)	122 lm	3,3%
Very high(80-90°)	13 lm	0,3%
Uplight		
Low(90-100°)	2 lm	0,1%
High(100-180°)	17 lm	0,4%

IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B2 U2 G1



Light Measurement Report

Print date: 21-5-2025

Measurement date and time: 21-5-2025 09:05:08 – Measurement no. VFR-250521-1342-MS

Measurement tracking No. and Link: [VT250521-002630](#)

Operator:




Power Details

Input Power

Power feed to light source	35,1 W
Frequency of input power	50 Hz
RMS Input voltage feed, V_{RMS}	230 V
RMS Input current feed, I_{RMS}	0,158 A
Volt-Ampere or apparent power = $V_{RMS} * I_{RMS}$	36,25 VA
Displacement factor of AC power feed	0,97
Power factor of AC current feed	0,97
Total harmonic distortion of the current	8,81%
Total harmonic distortion of the voltage	0,1%

Input Power Curve



Efficiency

Radiated power efficiency 33,7%



Lumen efficiency 106 lm/W



Stabilization Details

Warmup Conditions

Stable period	15 min
Stable change max	2,0%
Minimum time	15 min

Color Temperature Change

CCT start	6399 K
CCT shift	+101 K
CCT end	6500 K


Warmup Result

Total warmup time	Lamp stabilized in 17 min 30 sec
Warmup variation	-3,4%

Output Change

Output start	3862 lm
Output change	-127 lm
Output end	3735 lm

Stabilization Curve



Light Measurement Report

Print date: 21-5-2025

Measurement date and time: 21-5-2025 09:05:08 – Measurement no. VFR-250521-1342-MS

Measurement tracking No. and Link: [VT250521-002630](#)

Operator:



Flicker /TLA details

Flicker Meter Type Viso Systems LabFlicker
 Frequency of input power 50 Hz
 Flicker/TLA sample rate 20000 samples/s

Measurement time
 PstLM 180 sec
 All other indices 1,2 sec

Flicker indices according to Illuminating Engineering Society (IES)

Flicker frequency 100 Hz
 Percent Flicker 0,08 %
 Flicker index 0

Flicker indices according to California Energy Commission (CEC) 2016b

JA8/10 40 Hz 0,01 %
 JA8/10 90 Hz 0,01 %
 JA8/10 200 Hz 0,07 %
 JA8/10 400 Hz 0,07 %
 JA8/10 1000 Hz 0,07 %


TLA indices (re IEC TR 61547-1, IEC 61000-3-3 and IEC 61000-4-15)

PstLM value (F < 80 Hz) 0,01
 SVM value (80 < F < 2000 Hz) 0

Flicker indices according to Lighting Research Center (2015)

Perception metric, Assist Mp 0

Flicker frame (frame of one flicker period in time domain)



Flicker FFT (flicker curve in frequency domain)



IEEE 1789 Frequency/modulation plot

