

Light Measurement Report

Print date: 25-9-2025

Measurement date and time: 25-9-2025 14:43:39 – Measurement no. VFR-250925-3371-MS

Measurement tracking No. and Link: [VT250925-001446](#)

Operator:



Laboratory and Equipment

Laboratory Owner and Location
Goniospectrometer System and Type
Sensor Name, Calibr. Date and Serial No.
Spectrometer Manufacturer and Model

Viso Systems, Copenhagen V, Denmark
LabSpion – Type C, horizontal
LabSensor Model2 – 11-1-2024 – 3130191315
Ibsen Photonics, Denmark – Freedom VIS (Custom Viso)

Measurement Conditions

Number of C-planes and Resolution
 γ (gamma)-Resolution
Test Distance
Input Power, Power and Displ. Factors
Input RMS Voltage and Current
Frequency of Input Power
Warm-up Time and Variation

28 planes – 12,86°
5°
2,89 m
115,2 W – PF 0,98 – DPF 0,98
230 V – 0,512 A
50 Hz
Lamp stabilized in 15 min 1 sec – 2,0%

Tested Light Source



Product Name
Item No. and Manufacturer
Product Description (line 1)
SWITCH

812720-6000K-120W
812720-6000K-120W – Dutchfulfillment
LED HIGHBAY ARGOS | 0-10V | 150W/120W/100W | 60°/90°/120° | CCT

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)
Efficiency
Peak Intensity and Beam Angle
Correlated Color Temperature, Target/Measured
Color Rendering Index
Color Rendering TM30-18
Color Shift, CIE duv and MacAdam Steps
Flicker

15555 lm – 0,17% / 99,83%
135 lm/W
5415 cd – 114,4°
CCT = 6000 K / 5841 K
CRI 73,8
 R_f 74,3 – R_g 94,6
Duv 0,0012 – SDCM 2,5
SVM 0 – PstLM 0,1



Light Measurement Report

Print date: 25-9-2025

Measurement date and time: 25-9-2025 14:43:39 – Measurement no. VFR-250925-3371-MS


Measurement tracking No. and Link: [VT250925-001446](#)

Operator:



Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	15555 lm
Lumen Up% / Down%	0,17% / 99,83%
Peak Intensity	5415 cd
Beam Angle (50%)	114,4°
Beam Angle (90%)	115,8°
Beam Angle (10%)	113,3°

Cut-off Angle

Average 2,5%	171,9°
--------------	--------

Field Angle

Average 10%	148,4°
-------------	--------


Intensity Ratio

In 120° cone	86,8%
In 90° cone	54,9%

C000-C180

C090-C270

Linear distribution diagram - Intensity (candela) vs γ -angle



Light Measurement Report

Print date: 25-9-2025


Measurement date and time: 25-9-2025 14:43:39 – Measurement no. VFR-250925-3371-MS

Measurement tracking No. and Link: [VT250925-001446](#)

Operator:




Iso-intensity Diagram (Iso-candela)



90 %	4858,5 cd
80 %	4318,7 cd
70 %	3778,9 cd
60 %	3239,0 cd
50 %	2699,2 cd
40 %	2159,4 cd
30 %	1619,5 cd
20 %	1079,7 cd
10 %	539,8 cd

Peak intensity: 5398,4 cd
Number of c-planes: 28

Iso-illuminance Diagram (Iso-lux)



50,0 %	265,8 lx
30,0 %	159,5 lx
10,0 %	53,2 lx
5,0 %	26,6 lx
3,0 %	15,9 lx

Peak illuminance: 531,5 lx
Mounting height: 3,0 m
Number of c-planes: 28

Light Measurement Report

Print date: 25-9-2025

Measurement date and time: 25-9-2025 14:43:39 – Measurement no. VFR-250925-3371-MS

Measurement tracking No. and Link: [VT250925-001446](#)

Operator:




Color details

Correlated Color Temperature, Target CCT = 6000 K
 Correlated Color Temperature, Measured CCT = 5841 K
 Color Rendering Index CRI 73,8
 Color Rendering Index, R9 (red component) R9 = -27,3
 Color Rendering TM30-18 R_f 74,3 – R_g 94,6
 Color Quality Scale CQS = 71,0

MacAdam Steps SDCM = 2,5
 Color coordinates CIE 1931 (x;y) = (0,322;0,332)
 Color coordinate CIEs 1960 (u;v) = (0,203;0,314)
 Color deviation from BBL Duv = 0,0012
 Color coordinate CIEs 1976 (CIELUV) (u';v') = (0,203;0,471)


CIE 1931



CIE 1931 – zoomed on Planckian locus




Color Rendering Index per reference color (CIE 1995)




CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
71,9	78,0	81,4	75,2	72,9	69,8	81,4	59,6	-27,3	46,9	73,3	45,8	72,8	89,6	65,4

Spectral power distribution (SPD) / W/nm – 0-100%




TM30-18 Rf-values per hue bin



TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
67,8	75,3	64,1	72,0	76,8	87,0	89,4	80,3	80,0	62,9	58,5	75,6	82,4	78,2	69,8	78,7

Color Quality Scale by reference color



CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
79,5	93,6	63,2	58,0	69,0	73,4	77,8	85,7	90,6	73,4	67,7	68,2	70,4	57,7	66,4

Light Measurement Report

Print date: 25-9-2025


Measurement date and time: 25-9-2025 14:43:39 – Measurement no. VFR-250925-3371-MS

Measurement tracking No. and Link: [VT250925-001446](https://www.viso-systems.com/VT250925-001446)

Operator:



Beam Details



Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3,3	6,6	9,8	13,1	16,4	19,7	23	26,2	29,5	32,8	36,1	39,4	42,7	45,9	49,2	52,5	55,8	59,1	62,3	65,6	ft
4776	1194	531	299	191	133	97	75	59	48	39	33	28	24	21	19	17	15	13	12	lux
443,7	110,9	49,3	27,7	17,7	12,3	9,1	6,9	5,5	4,4	3,7	3,1	2,6	2,3	2	1,7	1,5	1,4	1,2	1,1	fc

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
4776	4756	4712	4636	4553	4483	4454	4616	5052	5345	4618	3123	2057	1329	786	481	298	163	59	10	cd
100%	100%	99%	97%	95%	94%	93%	97%	106%	112%	97%	65%	43%	28%	16%	10%	6%	3%	1%	0%	of 0°val

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
4776	4754	4693	4606	4506	4415	4361	4433	4710	4927	4390	3150	2134	1395	828	491	285	147	52	8	cd
100%	100%	98%	96%	94%	92%	91%	93%	99%	103%	92%	66%	45%	29%	17%	10%	6%	3%	1%	0%	of 0°val

Intensities in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
4776	4756	4712	4636	4553	4483	4454	4616	5052	5345	4618	3123	2057	1329	786	481	298	163	59	10	cd
100%	100%	99%	97%	95%	94%	93%	97%	106%	112%	97%	65%	43%	28%	16%	10%	6%	3%	1%	0%	of 0°val

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
4776	4754	4693	4606	4506	4415	4361	4433	4710	4927	4390	3150	2134	1395	828	491	285	147	52	8	cd
100%	100%	98%	96%	94%	92%	91%	93%	99%	103%	92%	66%	45%	29%	17%	10%	6%	3%	1%	0%	of 0°val

Light Measurement Report

Print date: 25-9-2025

Measurement date and time: 25-9-2025 14:43:39 – Measurement no. VFR-250925-3371-MS

Measurement tracking No. and Link: [VT250925-001446](#)

Operator:



Light Planning – UGR table

Uncorrected, comprehensive UGR table according to 117-1995

Reflectances		70	70	50	50	30	70	70	50	50	30
	ρ Ceiling	70	70	50	50	30	70	70	50	50	30
	ρ Walls	50	30	50	30	30	50	30	50	30	30
	ρ Floor	20	20	20	20	20	20	20	20	20	20
Room size		Viewed Crosswise					Viewed Endwise				
H = mounting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	Y										
2H	2H	32,4	33,6	32,6	33,9	34,1	32,4	33,5	32,6	33,9	34,1
	3H	32,7	33,9	33,1	34,2	34,4	32,8	34,0	33,2	34,3	34,5
	4H	32,9	34,0	33,3	34,3	34,5	32,9	34,1	33,3	34,3	34,6
	6H	33,0	34,0	33,3	34,3	34,7	33,1	34,1	33,4	34,4	34,7
	8H	33,0	34,0	33,4	34,3	34,7	33,1	34,1	33,4	34,4	34,8
	12H	33,0	34,0	33,4	34,3	34,8	33,1	34,0	33,5	34,4	34,8
4H	2H	32,6	33,8	33,0	34,0	34,3	32,6	33,7	33,0	34,0	34,3
	3H	33,2	34,1	33,6	34,5	34,9	33,2	34,2	33,6	34,5	35,0
	4H	33,3	34,2	33,8	34,6	35,1	33,4	34,3	33,8	34,7	35,2
	6H	33,5	34,3	34,0	34,7	35,0	33,5	34,4	34,0	34,7	35,1
	8H	33,5	34,3	34,1	34,7	35,1	33,6	34,4	34,1	34,7	35,1
	12H	33,6	34,2	34,1	34,6	35,1	33,6	34,3	34,1	34,7	35,2
8H	4H	33,4	34,1	33,9	34,5	34,9	33,4	34,2	33,9	34,6	34,9
	6H	33,6	34,2	34,1	34,7	35,2	33,7	34,2	34,2	34,7	35,3
	8H	33,8	34,3	34,3	34,8	35,4	33,8	34,3	34,3	34,8	35,5
	12H	33,9	34,3	34,5	34,8	35,4	33,9	34,3	34,5	34,8	35,4
12H	4H	33,3	34,0	33,8	34,4	34,9	33,4	34,0	33,9	34,5	34,9
	6H	33,7	34,2	34,2	34,7	35,3	33,7	34,2	34,2	34,7	35,4
	8H	33,8	34,2	34,4	34,7	35,3	33,8	34,3	34,4	34,8	35,4

Variations with the observer position for the luminaire spacings, S:

S = 1.0H	0,4 / -0,4	0,4 / -0,3
S = 1.5H	1,2 / -1,2	1,1 / -1,1
S = 2.0H	2,2 / -2,3	2,1 / -2,1

Coefficients of Utilization

Ceiling reflectance	80			70			50			30			10			0		
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumen delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	106	106	106	102	102	102	100	
1	110	105	101	98	107	103	99	96	99	96	93	95	93	90	91	89	88	86
2	100	92	86	81	98	91	85	80	87	82	78	84	80	76	81	77	74	72
3	91	81	74	67	89	80	73	67	77	71	66	74	69	64	72	67	63	61
4	84	72	63	57	81	71	63	57	68	61	56	66	60	55	64	58	54	52
5	77	64	55	49	75	63	55	48	61	53	48	59	52	47	57	51	47	45
6	71	57	49	42	69	56	48	42	55	47	42	53	46	41	51	45	41	39
7	65	52	43	37	63	51	43	37	49	42	36	48	41	36	47	40	36	34
8	60	47	38	33	59	46	38	32	45	37	32	44	37	32	42	36	32	30
9	56	43	35	29	55	42	34	29	41	34	29	40	33	29	39	33	28	27
10	53	39	31	26	51	39	31	26	38	31	26	37	30	26	36	30	26	24

Light Measurement Report

Print date: 25-9-2025

Measurement date and time: 25-9-2025 14:43:39 – Measurement no. VFR-250925-3371-MS

Measurement tracking No. and Link: [VT250925-001446](#)


Operator:



Luminaire budgetary diagram

Uncorrected, comprehensive UGR table according to 117-1995

LAMPS (number of lamps)



Conditions

H = Room height	Flux = 15555 lm				
H _{down} = Lamp distance from ceiling =	0.00 m	Line type	Ceiling reflectance	ρ(%) Wall reflectance	Floor reflectance
H _{work} = Work area height from floor =	0.00 m	-----	70	50	30
E _{work} = Average lux on work area =	100 lx	—————	50	30	20

Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
453 lm	1307 lm	2054 lm	2837 lm	4001 lm	2848 lm	1346 lm	517 lm	167 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
10,7 lm	1,22 lm	2,27 lm	2,83 lm	2,83 lm	2,45 lm	1,87 lm	1,16 lm	0,402 lm

Light Measurement Report

Print date: 25-9-2025

Measurement date and time: 25-9-2025 14:43:39 – Measurement no. VFR-250925-3371-MS

Measurement tracking No. and Link: [VT250925-001446](#)

Operator:



Outdoor Light Planning

Lumen per Zone

Zone (γ)	Lumen	% Total
0-10°	453 lm	2,9%
10-20°	1307 lm	8,4%
20-30°	2054 lm	13,2%
30-40°	2837 lm	18,2%
40-50°	4001 lm	25,7%
50-60°	2848 lm	18,3%
60-70°	1346 lm	8,7%
70-80°	517 lm	3,3%
80-90°	167 lm	1,1%
90-100°	11 lm	0,1%
100-110°	1 lm	0,0%
110-120°	2 lm	0,0%
120-130°	3 lm	0,0%
130-140°	3 lm	0,0%
140-150°	2 lm	0,0%
150-160°	2 lm	0,0%
160-170°	1 lm	0,0%
170-180°	0 lm	0,0%
Total	15555 lm	100,0%

Intensity peaks

Max intensity	5415 cd
Intensity, 90°	59 cd
Intensity, 0°	4776 cd

Zonal Lumen summary


Zone (γ)	Lumen	% Total
0-30°	3814 lm	24,5%
0-40°	6651 lm	42,8%
0-60°	13499 lm	86,8%
60-90°	2031 lm	13,1%
70-100°	695 lm	4,5%
90-120°	14 lm	0,1%
0-90°	15530 lm	99,8%
90-180°	26 lm	0,2%
0-180°	15555 lm	100,0%

BUG rating

	Lumen	% Total
Forward light		
Low(0-30°)	1907 lm	12,3%
Medium(30-60°)	4819 lm	31,0%
High(60-80°)	951 lm	6,1%
Very high(80-90°)	87 lm	0,6%
Back light		
Low(0-30°)	1907 lm	12,3%
Medium(30-60°)	4819 lm	31,0%
High(60-80°)	951 lm	6,1%
Very high(80-90°)	87 lm	0,6%
Uplight		
Low(90-100°)	15 lm	0,1%
High(100-180°)	15 lm	0,1%

IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B3 U2 G1



Light Measurement Report

Print date: 25-9-2025

Measurement date and time: 25-9-2025 14:43:39 – Measurement no. VFR-250925-3371-MS

Measurement tracking No. and Link: [VT250925-001446](#)

Operator:




Power Details


Input Power

Power feed to light source	115,2 W
Frequency of input power	50 Hz
RMS Input voltage feed, V_{RMS}	230 V
RMS Input current feed, I_{RMS}	0,512 A
Volt-Ampere or apparent power = $V_{RMS} * I_{RMS}$	117,69 VA
Displacement factor of AC power feed	0,98
Power factor of AC current feed	0,98
Total harmonic distortion of the current	4,4%
Total harmonic distortion of the voltage	0,06%

Input Power Curve



Efficiency



Stabilization Details

Warmup Conditions

Stable period	15 min
Stable change max	2,0%
Minimum time	15 min

Color Temperature Change

CCT start	5988 K
CCT shift	+12 K
CCT end	6000 K


Warmup Result

Total warmup time	Lamp stabilized in 15 min 1 sec
Warmup variation	-0,4%

Output Change

Output start	15608 lm
Output change	-52 lm
Output end	15555 lm

Stabilization Curve



Light Measurement Report

Print date: 25-9-2025

Measurement date and time: 25-9-2025 14:43:39 – Measurement no. VFR-250925-3371-MS

Measurement tracking No. and Link: [VT250925-001446](https://www.viso-systems.com/VT250925-001446)

Operator:



Flicker /TLA details

Flicker Meter Type Viso Systems LabFlicker
 Frequency of input power 50 Hz
 Flicker/TLA sample rate 40000 samples/s

Measurement time
 PstLM 180 sec
 All other indices 1,2 sec

Flicker indices according to Illuminating Engineering Society (IES)

Flicker frequency 160,64 Hz
 Percent Flicker 0,29 %
 Flicker index 0

Flicker indices according to California Energy Commission (CEC) 2016b

JA8/10 40 Hz n/a %
 JA8/10 90 Hz n/a %
 JA8/10 200 Hz n/a %
 JA8/10 400 Hz n/a %
 JA8/10 1000 Hz n/a %


TLA indices (re IEC TR 61547-1, IEC 61000-3-3 and IEC 61000-4-15)

PstLM value (F < 80 Hz) 0,1
 SVM value (80 < F < 2000 Hz) 0

Flicker indices according to Lighting Research Center (2015)

Perception metric, Assist Mp n/a

Flicker frame (frame of one flicker period in time domain)



Flicker FFT (flicker curve in frequency domain)



IEEE 1789 Frequency/modulation plot

