

# Light Measurement Report

Print date: 5-9-2025

Measurement date and time: 5-9-2025 11:09:40 – Measurement no. VFR-250905-2975-MS

Measurement tracking No. and Link: [VT250905-006819](#)

Operator:



## Laboratory and Equipment

Laboratory Owner and Location  
Goniospectrometer System and Type  
Sensor Name, Calibr. Date and Serial No.  
Spectrometer Manufacturer and Model

Viso Systems, Copenhagen V, Denmark  
LabSpion – Type C, horizontal  
LabSensor Model2 – 11-1-2024 – 3130191315  
Ibsen Photonics, Denmark – Freedom VIS (Custom Viso)

## Measurement Conditions

Number of C-planes and Resolution  
 $\gamma$  (gamma)-Resolution  
Test Distance  
Input Power, Power and Displ. Factors  
Input RMS Voltage and Current  
Frequency of Input Power  
Warm-up Time and Variation

36 planes – 10°  
5°  
12,09 m  
77,8 W – PF 0,98 – DPF 0,98  
230 V – 0,346 A  
50 Hz  
Lamp stabilized in 15 min 1 sec – 2,0%

## Tested Light Source


Product Name  
Item No. and Manufacturer  
Product Description (line 1)

813772-6500K  
81813772-6500K – Dutchfulfillment  
LICHTLIJN MODULE | JUPITER | 65-80W | 60° | CCT-SWITCH

## Main Light Measurement Results

Output – Total Lumen (Up% / Down%)  
Efficiency  
Peak Intensity and Beam Angle  
Correlated Color Temperature, Target/Measured  
Color Rendering Index  
Color Rendering TM30-18  
Color Shift, CIE duv and MacAdam Steps  
Flicker

12594 lm – 0,99% / 99,01%  
162 lm/W  
7326 cd – 78,3°  
CCT = 6500 K / 6376 K  
CRI 83,8  
 $R_f$  83,6 –  $R_g$  96,3  
Duv 0,0083 – SDCM 11,3  
SVM 0,01 – PstLM 0,01



# Light Measurement Report

Print date: 5-9-2025

Measurement date and time: 5-9-2025 11:09:40 – Measurement no. VFR-250905-2975-MS


Measurement tracking No. and Link: [VT250905-006819](#)

Operator:



## Luminous Intensity diagram

Unit: 0-100% of peak intensity



## Main Values

Output (total Lumen)	12594 lm
Lumen Up% / Down%	0,99% / 99,01%
Peak Intensity	7326 cd
Beam Angle (50%)	78,3°
Beam Angle (90%)	59,8°
Beam Angle (10%)	107,3°

## Cut-off Angle

Average 2,5%	158,4°
--------------	--------

## Field Angle

Average 10%	119,3°
-------------	--------


## Intensity Ratio

In 120° cone	89,6%
In 90° cone	72,5%

**C000-C180**

**C090-C270**

## Linear distribution diagram - Intensity (candela) vs $\gamma$ -angle



# Light Measurement Report

Print date: 5-9-2025


Measurement date and time: 5-9-2025 11:09:40 – Measurement no. VFR-250905-2975-MS

Measurement tracking No. and Link: [VT250905-006819](https://www.viso-systems.com/VT250905-006819)

Operator:




## Iso-intensity Diagram (Iso-candela)



90 %	6589,7 cd
80 %	5857,5 cd
70 %	5125,4 cd
60 %	4393,2 cd
50 %	3661,0 cd
40 %	2928,8 cd
30 %	2196,6 cd
20 %	1464,4 cd
10 %	732,2 cd

Peak intensity: 7321,9 cd  
Number of c-planes: 36

## Iso-illuminance Diagram (Iso-lux)



50,0 %	406,7 lx
30,0 %	244,0 lx
10,0 %	81,3 lx
5,0 %	40,7 lx
3,0 %	24,4 lx

Peak illuminance: 813,3 lx  
Mounting height: 3,0 m  
Number of c-planes: 36

# Light Measurement Report

Print date: 5-9-2025

Measurement date and time: 5-9-2025 11:09:40 – Measurement no. VFR-250905-2975-MS

Measurement tracking No. and Link: [VT250905-006819](#)

Operator:




## Color details


Correlated Color Temperature, Target CCT = 6500 K  
 Correlated Color Temperature, Measured CCT = 6376 K  
 Color Rendering Index CRI 83,8  
 Color Rendering Index, R9 (red component) R9 = 35,7  
 Color Rendering TM30-18 R<sub>f</sub> 83,6 – R<sub>g</sub> 96,3  
 Color Quality Scale CQS = 83,3

MacAdam Steps  
 Color coordinates CIE 1931 (x;y) = (0,314;0,324)  
 Color coordinate CIEs 1960 (u;v) = (0,200;0,310)  
 Color deviation from BBL Duv = 0,0083  
 Color coordinate CIEs 1976 (CIELUV) (u';v') = (0,200;0,466)


### CIE 1931



### CIE 1931 – zoomed on Planckian locus




### Color Rendering Index per reference color (CIE 1995)




CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
82,9	85,1	84,8	84,3	81,7	79,2	92,0	80,7	35,7	62,9	81,7	49,2	83,0	91,4	80,5

### Spectral power distribution (SPD) / W/nm – 0-100%




### TM30-18 Rf-values per hue bin



TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
81,4	87,7	82,4	85,0	85,6	92,5	93,1	85,7	83,4	69,8	72,1	86,9	88,3	86,0	75,4	87,0

### Color Quality Scale by reference color



CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
88,6	98,0	74,8	70,9	78,8	81,8	85,5	91,3	93,2	84,8	83,6	85,9	87,7	81,3	83,8

# Light Measurement Report

Print date: 5-9-2025


Measurement date and time: 5-9-2025 11:09:40 – Measurement no. VFR-250905-2975-MS

Measurement tracking No. and Link: [VT250905-006819](#)

Operator:



## Beam Details



### Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3,3	6,6	9,8	13,1	16,4	19,7	23	26,2	29,5	32,8	36,1	39,4	42,7	45,9	49,2	52,5	55,8	59,1	62,3	65,6	ft
7320	1830	813	457	293	203	149	114	90	73	60	51	43	37	33	29	25	23	20	18	lux
680	170	75,6	42,5	27,2	18,9	13,9	10,6	8,4	6,8	5,6	4,7	4	3,5	3	2,7	2,4	2,1	1,9	1,7	fc

### Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
7320	7309	7267	7188	7079	6939	6757	6519	6196	5734	5063	4155	3106	2111	1318	752	376	147	41	16	cd
100%	100%	99%	98%	97%	95%	92%	89%	85%	78%	69%	57%	42%	29%	18%	10%	5%	2%	1%	0%	of 0°val

### Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
7320	7264	7099	6756	6111	5038	3632	2361	1483	993	744	588	467	369	286	221	147	63	19	10	cd
100%	99%	97%	92%	83%	69%	50%	32%	20%	14%	10%	8%	6%	5%	4%	3%	2%	1%	0%	0%	of 0°val

### Intensities in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
7320	7309	7267	7188	7079	6939	6757	6519	6196	5734	5063	4155	3106	2111	1318	752	376	147	41	16	cd
100%	100%	99%	98%	97%	95%	92%	89%	85%	78%	69%	57%	42%	29%	18%	10%	5%	2%	1%	0%	of 0°val

### Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
7320	7264	7099	6756	6111	5038	3632	2361	1483	993	744	588	467	369	286	221	147	63	19	10	cd
100%	99%	97%	92%	83%	69%	50%	32%	20%	14%	10%	8%	6%	5%	4%	3%	2%	1%	0%	0%	of 0°val

# Light Measurement Report

Print date: 5-9-2025

Measurement date and time: 5-9-2025 11:09:40 – Measurement no. VFR-250905-2975-MS

Measurement tracking No. and Link: [VT250905-006819](https://www.viso-systems.com/VT250905-006819)

Operator:



## Light Planning – UGR table

Uncorrected, comprehensive UGR table according to 117-1995

Reflectances		70	70	50	50	30	70	70	50	50	30
	ρ Ceiling	70	70	50	50	30	70	70	50	50	30
	ρ Walls	50	30	50	30	30	50	30	50	30	30
	ρ Floor	20	20	20	20	20	20	20	20	20	20
Room size		Viewed Crosswise					Viewed Endwise				
H = mounting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	Y										
2H	2H	28,2	29,2	28,4	29,5	29,7	20,2	21,1	20,4	21,4	21,7
	3H	29,0	30,0	29,4	30,3	30,5	20,8	21,8	21,2	22,1	22,3
	4H	29,3	30,3	29,7	30,5	30,8	21,2	22,2	21,6	22,5	22,7
	6H	29,5	30,3	29,8	30,6	31,0	21,6	22,5	22,0	22,8	23,2
	8H	29,5	30,3	29,8	30,7	31,1	21,8	22,6	22,1	22,9	23,3
	12H	29,5	30,3	29,9	30,6	31,1	21,8	22,7	22,2	23,0	23,5
4H	2H	28,0	28,9	28,4	29,2	29,5	20,7	21,7	21,1	21,9	22,2
	3H	29,0	29,8	29,3	30,1	30,6	21,5	22,3	21,9	22,7	23,2
	4H	29,2	30,0	29,7	30,4	30,9	22,0	22,7	22,4	23,1	23,7
	6H	29,4	30,2	29,9	30,5	30,9	22,4	23,2	22,9	23,5	23,9
	8H	29,5	30,1	30,0	30,5	30,9	22,6	23,3	23,1	23,6	24,0
	12H	29,5	30,0	30,0	30,4	30,9	22,7	23,3	23,3	23,7	24,2
8H	4H	29,1	29,8	29,7	30,2	30,6	22,2	22,8	22,7	23,2	23,6
	6H	29,4	29,9	29,9	30,3	30,9	22,8	23,2	23,3	23,7	24,3
	8H	29,5	29,9	30,0	30,4	31,1	23,1	23,5	23,6	24,0	24,6
	12H	29,5	29,9	30,1	30,4	31,0	23,2	23,6	23,8	24,1	24,7
12H	4H	29,1	29,6	29,6	30,1	30,5	22,2	22,7	22,7	23,2	23,6
	6H	29,4	29,8	29,9	30,3	31,0	22,8	23,2	23,4	23,8	24,4
	8H	29,5	29,8	30,1	30,3	30,9	23,1	23,4	23,7	24,0	24,6

### Variations with the observer position for the luminaire spacings, S:

S = 1.0H	0,6 / -0,8	0,8 / -0,7
S = 1.5H	1,9 / -2,2	1,5 / -1,0
S = 2.0H	3,3 / -3,5	2,2 / -1,4

## Coefficients of Utilization

Ceiling reflectance	80			70			50			30			10			0		
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)																	
	Room Values are expressed as percentage of Lumen delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	106	106	106	101	101	101	99	
1	111	107	104	101	108	105	102	99	100	98	96	96	94	93	93	91	90	88
2	103	96	91	86	100	94	89	85	91	86	83	87	84	81	84	82	79	77
3	95	87	80	75	93	85	79	74	82	77	73	79	75	71	77	73	70	68
4	89	79	71	66	87	77	70	65	75	69	64	73	67	63	70	66	62	61
5	83	72	64	58	81	71	63	58	68	62	57	67	61	57	65	60	56	54
6	77	66	58	52	75	65	57	52	63	56	52	61	56	51	60	55	51	49
7	72	60	53	47	71	60	52	47	58	52	47	57	51	46	55	50	46	44
8	68	56	48	43	66	55	48	43	54	47	43	53	47	42	51	46	42	40
9	64	52	44	40	62	51	44	39	50	44	39	49	43	39	48	43	39	37
10	60	48	41	36	59	48	41	36	47	40	36	46	40	36	45	40	36	34

# Light Measurement Report

Print date: 5-9-2025

Measurement date and time: 5-9-2025 11:09:40 – Measurement no. VFR-250905-2975-MS

Measurement tracking No. and Link: [VT250905-006819](#)


Operator:



## Luminaire budgetary diagram

Uncorrected, comprehensive UGR table according to 117-1995

LAMPS (number of lamps)



### Conditions

H = Room height	Flux = 12594 lm				
H <sub>down</sub> = Lamp distance from ceiling =	0.00 m	Line type	Ceiling reflectance	ρ(%) Wall reflectance	Floor reflectance
H <sub>work</sub> = Work area height from floor =	0.00 m	-----	70	50	30
E <sub>work</sub> = Average lux on work area =	100 lx	—————	50	30	20

### Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
694 lm	1971 lm	2767 lm	2630 lm	1951 lm	1276 lm	731 lm	350 lm	98,0 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
15,1 lm	15,6 lm	17,3 lm	18,1 lm	18,0 lm	16,3 lm	13,1 lm	8,51 lm	2,98 lm

# Light Measurement Report

Print date: 5-9-2025

Measurement date and time: 5-9-2025 11:09:40 – Measurement no. VFR-250905-2975-MS

Measurement tracking No. and Link: [VT250905-006819](#)

Operator:



## Outdoor Light Planning

### Lumen per Zone

Zone (γ)	Lumen	% Total
0-10°	{LUM00-10} lm	#VALUE!
10-20°	{LUM10-20} lm	#VALUE!
20-30°	{LUM20-30} lm	#VALUE!
30-40°	{LUM30-40} lm	#VALUE!
40-50°	{LUM40-50} lm	#VALUE!
50-60°	{LUM50-60} lm	#VALUE!
60-70°	{LUM60-70} lm	#VALUE!
70-80°	{LUM70-80} lm	#VALUE!
80-90°	{LUM80-90} lm	#VALUE!
90-100°	{LUM90-100} lm	#VALUE!
100-110°	{LUM100-110} lm	#VALUE!
110-120°	{LUM110-120} lm	#VALUE!
120-130°	{LUM120-130} lm	#VALUE!
130-140°	{LUM130-140} lm	#VALUE!
140-150°	{LUM140-150} lm	#VALUE!
150-160°	{LUM150-160} lm	#VALUE!
160-170°	{LUM160-170} lm	#VALUE!
170-180°	{LUM170-180} lm	#VALUE!
Total	0 lm	#VALUE!

### Intensity peaks

Max intensity	{PEAK} cd
Intensity, 90°	{INT90} cd
Intensity, 0°	{INT0} cd

### Zonal Lumen summary

Zone (γ)	Lumen	% Total
0-30°	{LUM00-30} lm	#VALUE!
0-40°	{LUM00-40} lm	#VALUE!
0-60°	{LUM00-60} lm	#VALUE!
60-90°	{LUM60-90} lm	#VALUE!
70-100°	{LUM70-100} lm	#VALUE!
90-120°	{LUM90-120} lm	#VALUE!
0-90°	{LUM00-90} lm	#VALUE!
90-180°	{LUM90-180} lm	#VALUE!
0-180°	{LUM00-180} lm	#VALUE!

### BUG rating

	Lumen	% Total
<b>Forward light</b>		
Low(0-30°)	{BUG0} lm	#VALUE!
Medium(30-60°)	{BUG1} lm	#VALUE!
High(60-80°)	{BUG2} lm	#VALUE!
Very high(80-90°)	{BUG3} lm	#VALUE!

### Back light


Low(0-30°)	{BUG4} lm	#VALUE!
Medium(30-60°)	{BUG5} lm	#VALUE!
High(60-80°)	{BUG6} lm	#VALUE!
Very high(80-90°)	{BUG7} lm	#VALUE!

### Uplight

Low(90-100°)	{BUG8} lm	#VALUE!
High(100-180°)	{BUG9} lm	#VALUE!

## IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B4 U3 G1



# Light Measurement Report

Print date: 5-9-2025

Measurement date and time: 5-9-2025 11:09:40 – Measurement no. VFR-250905-2975-MS

Measurement tracking No. and Link: [VT250905-006819](#)

Operator:




## Power Details


### Input Power

Power feed to light source	77,8 W
Frequency of input power	50 Hz
RMS Input voltage feed, $V_{RMS}$	230 V
RMS Input current feed, $I_{RMS}$	0,346 A
Volt-Ampere or apparent power = $V_{RMS} * I_{RMS}$	79,56 VA
Displacement factor of AC power feed	0,98
Power factor of AC current feed	0,98
Total harmonic distortion of the current	8,25%
Total harmonic distortion of the voltage	0,08%

### Input Power Curve



### Efficiency



## Stabilization Details

### Warmup Conditions

Stable period	15 min
Stable change max	2,0%
Minimum time	15 min

### Color Temperature Change

CCT start	6491 K
CCT shift	+9 K
CCT end	6500 K


### Warmup Result

Total warmup time	Lamp stabilized in 15 min 1 sec
Warmup variation	-1,0%

### Output Change

Output start	12718 lm
Output change	-124 lm
Output end	12594 lm

### Stabilization Curve



# Light Measurement Report

Print date: 5-9-2025

Measurement date and time: 5-9-2025 11:09:40 – Measurement no. VFR-250905-2975-MS

Measurement tracking No. and Link: [VT250905-006819](https://www.viso-systems.com/VT250905-006819)

Operator:



## Flicker /TLA details

Flicker Meter Type: Viso Systems LabFlicker  
 Frequency of input power: 50 Hz  
 Flicker/TLA sample rate: 20000 samples/s

**Measurement time**  
 PstLM: 180 sec  
 All other indices: 1,2 sec

### Flicker indices according to Illuminating Engineering Society (IES)

Flicker frequency: 102,04 Hz  
 Percent Flicker: 0,17 %  
 Flicker index: 0

### Flicker indices according to California Energy Commission (CEC) 2016b

JA8/10 40 Hz: 0,01 %  
 JA8/10 90 Hz: 0,01 %  
 JA8/10 200 Hz: 0,15 %  
 JA8/10 400 Hz: 0,16 %  
 JA8/10 1000 Hz: 0,16 %


### TLA indices (re IEC TR 61547-1, IEC 61000-3-3 and IEC 61000-4-15)

PstLM value (F < 80 Hz): 0,01  
 SVM value (80 < F < 2000 Hz): 0,01


### Flicker indices according to Lighting Research Center (2015)

Perception metric, Assist Mp: 0,01

### Flicker frame (frame of one flicker period in time domain)



### Flicker FFT (flicker curve in frequency domain)



### IEEE 1789 Frequency/modulation plot

