

Light Measurement Report

Print date: 16-9-2025

Measurement date and time: 16-9-2025 10:41:42 – Measurement no. VFR-250916-3225-MS

Measurement tracking No. and Link: [VT250916-009235](#)

Operator:



Laboratory and Equipment

Laboratory Owner and Location
Goniospectrometer System and Type
Sensor Name, Calibr. Date and Serial No.
Spectrometer Manufacturer and Model

Viso Systems, Copenhagen V, Denmark
LabSpion – Type C, horizontal
LabSensor Model2 – 11-1-2024 – 3130191315
Ibsen Photonics, Denmark – Freedom VIS (Custom Viso)

Measurement Conditions

Number of C-planes and Resolution
 γ (gamma)-Resolution
Test Distance
Input Power, Power and Displ. Factors
Input RMS Voltage and Current
Frequency of Input Power
Warm-up Time and Variation

12 planes – 30°
5°
9,59 m
26,3 W – PF 0,97 – DPF 0,97
230 V – 0,118 A
50 Hz
Lamp stabilized in 16 min 18 sec – 2,0%

Tested Light Source



Product Name
Item No. and Manufacturer
Product Description (line 1)

813659-6000K-25W
813659-6000K-25W – Dutchfulfillment
LED BATTEN | CLIFF | 25-45W | 120CM | PHILIPS DRIVER | CCT-SWITCH

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)
Efficiency
Peak Intensity and Beam Angle
Correlated Color Temperature, Target/Measured
Color Rendering Index
Color Rendering TM30-18
Color Shift, CIE duv and MacAdam Steps
Flicker

3388 lm – 8,48% / 91,52%
129 lm/W
923 cd – 121,5°
CCT = 6000 K / 5858 K
CRI 82,6
 R_f 82,2 – R_g 93,7
Duv 0,0039 – SDCM 5,4
SVM 0,01 – PstLM 0,01



Light Measurement Report

Print date: 16-9-2025

Measurement date and time: 16-9-2025 10:41:42 – Measurement no. VFR-250916-3225-MS


Measurement tracking No. and Link: [VT250916-009235](https://vt250916-009235)

Operator:



Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	3388 lm
Lumen Up% / Down%	8,48% / 91,52%
Peak Intensity	923 cd
Beam Angle (50%)	121,5°
Beam Angle (90%)	121,5°
Beam Angle (10%)	121,5°

Cut-off Angle

Average 2,5%	242,7°
--------------	--------

Field Angle

Average 10%	202,7°
-------------	--------


Intensity Ratio

In 120° cone	63,7%
In 90° cone	42,4%

C000-C180

C090-C270

Linear distribution diagram - Intensity (candela) vs γ -angle



Light Measurement Report

Print date: 16-9-2025


Measurement date and time: 16-9-2025 10:41:42 – Measurement no. VFR-250916-3225-MS

Measurement tracking No. and Link: [VT250916-009235](https://www.viso-systems.com/VT250916-009235)

Operator:



Iso-intensity Diagram (Iso-candela)




90 %	830,8 cd
80 %	738,5 cd
70 %	646,2 cd
60 %	553,9 cd
50 %	461,6 cd
40 %	369,3 cd
30 %	276,9 cd
20 %	184,6 cd
10 %	92,3 cd

Peak intensity: 923,2 cd

Number of c-planes: 12

Iso-illuminance Diagram (Iso-lux)



50,0 %	51,3 lx
30,0 %	30,8 lx
10,0 %	10,3 lx
5,0 %	5,1 lx
3,0 %	3,1 lx

Peak illuminance: 102,6 lx

Mounting height: 3,0 m

Number of c-planes: 12

Light Measurement Report

Print date: 16-9-2025

Measurement date and time: 16-9-2025 10:41:42 – Measurement no. VFR-250916-3225-MS

Measurement tracking No. and Link: [VT250916-009235](#)

Operator:




Color details


Correlated Color Temperature, Target CCT = 6000 K
 Correlated Color Temperature, Measured CCT = 5858 K
 Color Rendering Index CRI 82,6
 Color Rendering Index, R9 (red component) R9 = 6,3
 Color Rendering TM30-18 R_f 82,2 – R_g 93,7
 Color Quality Scale CQS = 79,8

MacAdam Steps SDCM = 5,4
 Color coordinates CIE 1931 (x;y) = (0,322;0,332)
 Color coordinate CIEs 1960 (u;v) = (0,203;0,314)
 Color deviation from BBL Duv = 0,0039
 Color coordinate CIEs 1976 (CIELUV) (u';v') = (0,203;0,471)


CIE 1931



CIE 1931 – zoomed on Planckian locus




Color Rendering Index per reference color (CIE 1995)




CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
80,9	88,4	91,8	81,1	80,6	82,3	87,7	68,2	6,3	70,9	79,8	53,9	83,4	95,8	75,4

Spectral power distribution (SPD) / W/nm – 0-100%




TM30-18 R_f-values per hue bin



TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
74,8	83,5	79,9	86,1	86,7	92,8	91,6	83,9	81,4	71,2	72,6	89,4	86,9	83,4	71,1	84,8

Color Quality Scale by reference color



CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
82,0	98,5	75,7	68,9	75,4	78,9	84,1	88,7	96,3	86,1	81,6	80,9	81,1	69,9	74,8

Light Measurement Report

Print date: 16-9-2025


Measurement date and time: 16-9-2025 10:41:42 – Measurement no. VFR-250916-3225-MS

Measurement tracking No. and Link: [VT250916-009235](https://www.viso-systems.com/VT250916-009235)

Operator:



Beam Details



Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3,3	6,6	9,8	13,1	16,4	19,7	23	26,2	29,5	32,8	36,1	39,4	42,7	45,9	49,2	52,5	55,8	59,1	62,3	65,6	ft
923	231	103	58	37	26	19	14	11	9	8	6	5	5	4	4	3	3	3	2	lux
85,8	21,4	9,5	5,4	3,4	2,4	1,8	1,3	1,1	0,9	0,7	0,6	0,5	0,4	0,4	0,3	0,3	0,3	0,2	0,2	fc

Intensities in 0° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°	γ
923	910	873	814	736	643	541	435	331	237	161	105	63	33	15	7	6	5	5	5	cd
100%	99%	95%	88%	80%	70%	59%	47%	36%	26%	17%	11%	7%	4%	2%	1%	1%	1%	1%	1%	of 0°val

Intensities in 90° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°	γ
923	910	873	814	736	643	541	435	331	237	161	105	63	33	15	7	6	5	5	5	cd
100%	99%	95%	88%	80%	70%	59%	47%	36%	26%	17%	11%	7%	4%	2%	1%	1%	1%	1%	1%	of 0°val

Intensities in 180° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°	γ
923	910	873	814	736	643	541	435	331	237	161	105	63	33	15	7	6	5	5	5	cd
100%	99%	95%	88%	80%	70%	59%	47%	36%	26%	17%	11%	7%	4%	2%	1%	1%	1%	1%	1%	of 0°val

Intensities in 270° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°	γ
923	910	873	814	736	643	541	435	331	237	161	105	63	33	15	7	6	5	5	5	cd
100%	99%	95%	88%	80%	70%	59%	47%	36%	26%	17%	11%	7%	4%	2%	1%	1%	1%	1%	1%	of 0°val

Light Measurement Report

Print date: 16-9-2025

Measurement date and time: 16-9-2025 10:41:42 – Measurement no. VFR-250916-3225-MS

Measurement tracking No. and Link: [VT250916-009235](#)

Operator:



Light Planning – UGR table

Uncorrected, comprehensive UGR table according to 117-1995

Reflectances		70	70	50	50	30	70	70	50	50	30
	ρ Ceiling	70	70	50	50	30	70	70	50	50	30
	ρ Walls	50	30	50	30	30	50	30	50	30	30
	ρ Floor	20	20	20	20	20	20	20	20	20	20
Room size		Viewed Crosswise					Viewed Endwise				
H = mounting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	Y										
2H	2H	19,8	21,0	20,2	21,5	21,9	20,2	21,4	20,6	21,9	22,3
	3H	21,6	22,9	22,1	23,3	23,7	22,2	23,4	22,7	23,9	24,3
	4H	22,6	23,7	23,1	24,2	24,6	23,3	24,4	23,8	24,9	25,3
	6H	23,5	24,6	23,9	25,0	25,5	24,4	25,5	24,9	25,9	26,4
	8H	23,9	25,0	24,4	25,4	26,0	25,0	26,0	25,5	26,5	27,0
	12H	24,3	25,4	24,8	25,8	26,4	25,6	26,7	26,1	27,1	27,7
4H	2H	20,5	21,7	21,1	22,2	22,6	20,8	22,0	21,3	22,4	22,9
	3H	22,7	23,7	23,2	24,2	24,8	23,1	24,2	23,6	24,6	25,2
	4H	23,7	24,7	24,2	25,2	25,8	24,3	25,3	24,8	25,8	26,4
	6H	24,7	25,6	25,3	26,1	26,7	25,5	26,5	26,2	26,9	27,5
	8H	25,2	26,0	25,9	26,6	27,1	26,2	27,0	26,8	27,6	28,1
	12H	25,8	26,4	26,4	27,0	27,6	27,0	27,7	27,6	28,2	28,9
8H	4H	24,2	25,0	24,8	25,5	26,0	24,7	25,5	25,3	26,0	26,5
	6H	25,5	26,1	26,1	26,7	27,4	26,2	26,8	26,8	27,4	28,1
	8H	26,1	26,7	26,8	27,3	28,1	27,0	27,6	27,6	28,2	29,0
	12H	26,8	27,3	27,5	27,9	28,7	27,9	28,4	28,6	29,1	29,8
12H	4H	24,3	24,9	24,9	25,5	26,1	24,7	25,4	25,3	26,0	26,6
	6H	25,7	26,2	26,3	26,9	27,6	26,3	26,9	27,0	27,5	28,3
	8H	26,4	26,9	27,1	27,5	28,3	27,2	27,7	27,9	28,3	29,1

Variations with the observer position for the luminaire spacings, S:

S = 1.0H	0,1 / -0,1	0,1 / -0,1
S = 1.5H	0,1 / -0,1	0,1 / -0,1
S = 2.0H	0,2 / -0,2	0,2 / -0,2

Coefficients of Utilization

Ceiling reflectance	80			70			50			30			10			0		
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)																	
	Room Values are expressed as percentage of Lumen delivered to the task surface																	
0	117	117	117	117	113	113	113	113	106	106	106	100	100	100	94	94	94	92
1	104	99	93	89	101	95	91	87	90	86	82	84	81	78	79	77	74	72
2	94	85	77	71	91	82	75	69	77	71	66	72	68	63	68	64	61	58
3	85	74	65	58	82	71	63	57	67	60	55	63	57	53	60	55	51	48
4	78	65	56	48	75	63	54	48	59	52	46	56	50	44	53	47	43	40
5	71	58	48	41	69	56	47	41	53	45	39	50	43	38	47	42	37	35
6	66	52	43	36	63	50	42	35	48	40	34	45	38	33	43	37	32	30
7	61	47	38	31	59	46	37	31	43	36	30	41	34	29	39	33	29	26
8	57	43	34	28	55	42	33	28	40	32	27	38	31	26	36	30	26	23
9	53	39	31	25	51	38	30	25	36	29	24	35	28	24	33	27	23	21
10	50	36	28	23	48	35	28	22	34	27	22	32	26	21	31	25	21	19

Light Measurement Report

Print date: 16-9-2025

Measurement date and time: 16-9-2025 10:41:42 – Measurement no. VFR-250916-3225-MS

Measurement tracking No. and Link: [VT250916-009235](#)


Operator:



Luminaire budgetary diagram

Uncorrected, comprehensive UGR table according to 117-1995

LAMPS (number of lamps)



Conditions

H = Room height	Flux = 3388 lm				
H _{down} = Lamp distance from ceiling =	0.00 m	Line type	Ceiling reflectance	ρ(%) Wall reflectance	Floor reflectance
H _{work} = Work area height from floor =	0.00 m	-----	70	50	30
E _{work} = Average lux on work area =	100 lx	—————	50	30	20

Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
87,4 lm	251 lm	382 lm	467 lm	497 lm	474 lm	408 lm	316 lm	219 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
140 lm	80,0 lm	39,0 lm	15,1 lm	5,45 lm	3,55 lm	2,51 lm	1,50 lm	0,490 lm

Light Measurement Report

Print date: 16-9-2025

Measurement date and time: 16-9-2025 10:41:42 – Measurement no. VFR-250916-3225-MS

Measurement tracking No. and Link: [VT250916-009235](#)

Operator:



Outdoor Light Planning

Lumen per Zone

Zone (γ)	Lumen	% Total
0-10°	87 lm	2,6%
10-20°	251 lm	7,4%
20-30°	382 lm	11,3%
30-40°	467 lm	13,8%
40-50°	497 lm	14,7%
50-60°	474 lm	14,0%
60-70°	408 lm	12,0%
70-80°	316 lm	9,3%
80-90°	219 lm	6,5%
90-100°	140 lm	4,1%
100-110°	80 lm	2,4%
110-120°	39 lm	1,2%
120-130°	15 lm	0,4%
130-140°	5 lm	0,2%
140-150°	4 lm	0,1%
150-160°	3 lm	0,1%
160-170°	2 lm	0,0%
170-180°	0 lm	0,0%
Total	3388 lm	100,0%

Intensity peaks

Max intensity	923 cd
Intensity, 90°	161 cd
Intensity, 0°	923 cd

Zonal Lumen summary


Zone (γ)	Lumen	% Total
0-30°	721 lm	21,3%
0-40°	1188 lm	35,1%
0-60°	2158 lm	63,7%
60-90°	943 lm	27,8%
70-100°	674 lm	19,9%
90-120°	259 lm	7,6%
0-90°	3101 lm	91,5%
90-180°	287 lm	8,5%
0-180°	3388 lm	100,0%

BUG rating

	Lumen	% Total
Forward light		
Low(0-30°)	360 lm	10,6%
Medium(30-60°)	718 lm	21,2%
High(60-80°)	362 lm	10,7%
Very high(80-90°)	110 lm	3,2%
Back light		
Low(0-30°)	360 lm	10,6%
Medium(30-60°)	718 lm	21,2%
High(60-80°)	362 lm	10,7%
Very high(80-90°)	110 lm	3,2%
Uplight		
Low(90-100°)	140 lm	4,1%
High(100-180°)	149 lm	4,4%

IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B1 U3 G2



Light Measurement Report

Print date: 16-9-2025

Measurement date and time: 16-9-2025 10:41:42 – Measurement no. VFR-250916-3225-MS

Measurement tracking No. and Link: [VT250916-009235](#)

Operator:




Power Details


Input Power

Power feed to light source	26,3 W
Frequency of input power	50 Hz
RMS Input voltage feed, V_{RMS}	230 V
RMS Input current feed, I_{RMS}	0,118 A
Volt-Ampere or apparent power = $V_{RMS} * I_{RMS}$	27,16 VA
Displacement factor of AC power feed	0,97
Power factor of AC current feed	0,97
Total harmonic distortion of the current	6,57%
Total harmonic distortion of the voltage	0,13%

Input Power Curve



Efficiency



Stabilization Details

Warmup Conditions

Stable period	15 min
Stable change max	2,0%
Minimum time	15 min

Color Temperature Change

CCT start	6073 K
CCT shift	-73 K
CCT end	6000 K


Warmup Result

Total warmup time	Lamp stabilized in 16 min 18 sec
Warmup variation	+7,8%

Output Change

Output start	3335 lm
Output change	+53 lm
Output end	3388 lm

Stabilization Curve



Light Measurement Report

Print date: 16-9-2025

Measurement date and time: 16-9-2025 10:41:42 – Measurement no. VFR-250916-3225-MS

Measurement tracking No. and Link: [VT250916-009235](https://www.viso-systems.com/VT250916-009235)

Operator:



Flicker /TLA details

Flicker Meter Type: Viso Systems LabFlicker
 Frequency of input power: 50 Hz
 Flicker/TLA sample rate: 20000 samples/s

Measurement time
 PstLM: 180 sec
 All other indices: 1,2 sec

Flicker indices according to Illuminating Engineering Society (IES)

Flicker frequency: 100 Hz
 Percent Flicker: 0,29 %
 Flicker index: 0

Flicker indices according to California Energy Commission (CEC) 2016b

JA8/10 40 Hz: 0,01 %
 JA8/10 90 Hz: 0,05 %
 JA8/10 200 Hz: 0,27 %
 JA8/10 400 Hz: 0,28 %
 JA8/10 1000 Hz: 0,28 %


TLA indices (re IEC TR 61547-1, IEC 61000-3-3 and IEC 61000-4-15)

PstLM value (F < 80 Hz): 0,01
 SVM value (80 < F < 2000 Hz): 0,01

Flicker indices according to Lighting Research Center (2015)

Perception metric, Assist Mp: 0,01

Flicker frame (frame of one flicker period in time domain)



Flicker FFT (flicker curve in frequency domain)



IEEE 1789 Frequency/modulation plot

